



Installation of Apache OpenMeetings 3.3.2 on Ubuntu 16.04 LTS

This tutorial is made based on a fresh installations of

ubuntu-mate-16.04-desktop-amd64.iso

It is tested with positive result. We will use the Apache's binary version OpenMeetings 3.3.2 stable, that is to say will suppress his compilation. It is done step by step.

22-9-2017

Starting...

1)

First, we update and upgrade the OS:

```
sudo apt-get update
```

```
sudo apt-get upgrade
```

2)

----- **Installation of Oracle Java 1.8** -----


OpenMeetings **3.3.2** need Java **1.8** to work. So, we install Oracle Java 1.8:

```
sudo add-apt-repository ppa:webupd8team/java
```

```
sudo apt-get update
```

```
sudo apt-get install oracle-java8-installer
```

Will open a window. Press **Enter** accepting:



```
root@tub: /home/guadal
File Edit View Search Terminal Help
Package configuration


Configuring oracle-java8-installer

Oracle Binary Code License Agreement for the Java SE Platform Products
and JavaFX

You MUST agree to the license available in http://java.com/license if
you want to use Oracle JDK.

<Ok>
```

Will ask newly. Select **Yes** → **Enter**



```
root@tub: /home/guadal
File Edit View Search Terminal Help
Package configuration

Configuring oracle-java8-installer

In order to install this package, you must accept the license terms, the
"Oracle Binary Code License Agreement for the Java SE Platform Products
and JavaFX ". Not accepting will cancel the installation.

Do you accept the Oracle Binary Code license terms?

<Yes> <No>
```

Now, please, select Oracle Java, if you have more than one java versions installed. OpenJava give an error in some function of OpenMeetings. I've tested it:

```
sudo update-alternatives --config java
```

To see the active java version:

```
java -version
```

3)

----- Installation of LibreOffice -----

LibreOffice is need it to convert to pdf the uploaded office files.

The ubuntu desktop iso have already LibreOffice installed, but we do also for server iso:

```
sudo add-apt-repository ppa:libreoffice/ppa
```

```
sudo apt-get update
```

```
sudo apt-get install libreoffice
```

Now some kind of information only:

LibreOffice installation folder is /usr/lib/libreoffice.

4)

----- Installation ImageMagic, Sox and Swftools -----

ImageMagic, will work the image files, png, jpg, gif, etc. Will install it and some more libraries and paquets:

```
sudo apt-get install -y imagemagick libjpeg62 zlib1g-dev unzip make build-essential wget nmap
```

Sox, work the sound. We'll compile, because this version is newer than the repo:

```
cd /opt
```

```
wget http://sourceforge.net/projects/sox/files/sox/14.4.2/sox-14.4.2.tar.gz
```

```
tar xzvf sox-14.4.2.tar.gz
```

```
cd /opt/sox-14.4.2
```

```
./configure
```

```
make && make install
```

Swftools. LibreOffice convert to pdf the uploaded office files, and Swftools convert these pdf to swf, flash files, that later will show it in the whiteboard. Also convert jpg2swf, png2swf, gif2swf.

Don't use a newer swftools version. Surely, will have not pdf2swf.

```
sudo apt-get install libstreamer-plugins-base0.10-0 libstreamer0.10-0 libgif7 libzip-0-13
```

For 64 bit:

```
cd /opt
```

(Only one line without space between both)

```
wget http://mirrors.kernel.org/ubuntu/pool/universe/libo/liboil/liboil0.3_0.3.17-2ubuntu4_amd64.deb
```

```
dpkg -i liboil0.3_0.3.17-2ubuntu4_amd64.deb
```

(Only one line without space between both)

```
wget https://launchpad.net/ella-renaissance/ella-renaissance-beta/beta1/+download/swftools_0.9.1-1_amd64.deb
```

```
dpkg -i swftools_0.9.1-1_amd64.deb
```

```
echo "swftools hold" | sudo dpkg --set-selections (To block version)
```

For 32 bit:

```
cd /opt
```

```
wget http://mirrors.kernel.org/ubuntu/pool/universe/libo/liboil/liboil0.3_0.3.17-2ubuntu4_i386.deb
```

```
dpkg -i liboil0.3_0.3.17-2ubuntu4_i386.deb
```

(Only one line without space between both)

```
wget https://launchpad.net/ella-renaissance/ella-renaissance-beta/beta1/+download/swftools_0.9.1-1_i386.deb
```

```
dpkg -i swftools_0.9.1-1_i386.deb
```

```
echo "swftools hold" | sudo dpkg --set-selections (To block version)
```

5)

----- Installation of Adobe flash player -----

OpenMeetings even need Adobe Flash Player for rooms. We install it

```
sudo apt-get install flashplugin-installer
```

6)

----- Compilation of FFmpeg -----

FFmpeg will work with video.

This compilation is based on:

<https://trac.ffmpeg.org/wiki/CompilationGuide/Ubuntu>

Updated files to 22-9-2017. Install some libraries:

(Only one line with space between each one)

```
sudo apt-get -y --force-yes install autoconf automake build-essential libass-dev libfreetype6-dev
libgpac-dev libSDL1.2-dev libtheora-dev libtool libva-dev libvdpau-dev libvorbis-dev libxcb1-dev
libxcb-shm0-dev libxcb-xfixes0-dev pkg-config texi2html zlib1g-dev nasm libx264-dev cmake
mercurial libopus-dev curl git
```

I made a script that will download, compile and install ffmpeg.

The result of any recording we do in OpenMeetings, will be in mp4 format.

Please, download the script:

```
cd /opt
```

(Only one line without space between both)

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/ffmpeg-ubuntu-
debian.sh
```

...concede permission of execution:

```
chmod +x ffmpeg-ubuntu-debian.sh
```

...and run it (be connected to Internet). The compilation will spend about 30 minutes:

```
./ffmpeg-ubuntu-debian.sh
```

When finish the compilation, a text will announce it:

FFmpeg Compilation is Finished!

Then, please, go to **step 7**).

But if you prefer copy and paste (**i don't advise**), here are the commands script:

```
sudo gedit /opt/ffpmeg.sh
```

...copy and paste **from here**:

```
# FFmpeg compilation for Ubuntu and Debian.
# Alvaro Bustos. Thanks to Hunter.
# Updated 22-9-2017

sudo apt-get update
sudo apt-get -y --force-yes install autoconf automake build-essential libass-dev libfreetype6-dev
libsdl1.2-dev libtheora-dev libtool libva-dev libvdpau-dev libvorbis-dev libxcb1-dev libxcb-shm0-
dev libxcb-xfixes0-dev pkg-config texi2html zlib1g-dev mercurial cmake

# Create a directory for sources.
SOURCES=$(mkdir ~/ffmpeg_sources)
cd ~/ffmpeg_sources

# Download the necessary sources.
wget ftp://ftp.gnome.org/mirror/xbmc.org/build-deps/sources/lame-3.99.5.tar.gz
wget http://www.tortall.net/projects/yasm/releases/yasm-1.3.0.tar.gz
curl -#LO ftp://ftp.videolan.org/pub/x264/snapshots/last_stable_x264.tar.bz2
hg clone https://bitbucket.org/multicoreware/x265
wget -O fdk-aac.tar.gz https://github.com/mstorsjo/fdk-aac/tarball/master
wget http://downloads.xiph.org/releases/opus/opus-1.1.5.tar.gz
wget http://storage.googleapis.com/downloads.webmproject.org/releases/webm/libvpx-1.5.0.tar.bz2
git clone --depth 1 git://source.ffmpeg.org/ffmpeg

# Unpack files
for file in `ls ~/ffmpeg_sources/*.tar.*`; do
tar -xvf $file
done

cd yasm-*/
./configure --prefix="$HOME/ffmpeg_build" --bindir="$HOME/bin" && make && sudo make
install && make distclean; cd ..

cd x264-*/
PATH="$HOME/bin:$PATH" ./configure --prefix="$HOME/ffmpeg_build" --bindir="$HOME/bin"
--enable-static && PATH="$HOME/bin:$PATH" make && sudo make install && make distclean;
cd ..

cd x265/build/linux
PATH="$HOME/bin:$PATH" cmake -G "Unix Makefiles"
-DCMAKE_INSTALL_PREFIX="$HOME/ffmpeg_build" -DENABLE_SHARED:bool=off
../../source && make && sudo make install && make distclean; cd ~/ffmpeg_sources

cd mstorsjo-fdk-aac*
autoreconf -fiv && ./configure --prefix="$HOME/ffmpeg_build" --disable-shared && make &&
sudo make install && make distclean; cd ..
```

```
cd lame-*/
./configure --prefix="$HOME/ffmpeg_build" --enable-nasm --disable-shared && make && sudo
make install && make distclean; cd ..
```

```
cd opus-*/
./configure --prefix="$HOME/ffmpeg_build" --disable-shared && make && sudo make install &&
make distclean; cd ..
```

```
cd libvpx-*/
PATH="$HOME/bin:$PATH" ./configure --prefix="$HOME/ffmpeg_build" --disable-examples
--disable-unit-tests && PATH="$HOME/bin:$PATH" make && sudo make install && make clean;
cd ..
```

```
cd ffmpeg
PATH="$HOME/bin:$PATH" PKG_CONFIG_PATH="$HOME/ffmpeg_build/lib/pkgconfig"
./configure --prefix="$HOME/ffmpeg_build" --pkg-config-flags="--static" --extra-cflags="-
I$HOME/ffmpeg_build/include" --extra-ldflags="-L$HOME/ffmpeg_build/lib"
--bindir="$HOME/bin" --enable-gpl --enable-libass --enable-libfdk-aac --enable-libfreetype
--enable-libmp3lame --enable-libopus --enable-libtheora --enable-libvorbis --enable-libvpx
--enable-libx264 --enable-libx265 --enable-nonfree && PATH="$HOME/bin:$PATH" make &&
sudo make install && make distclean && hash -r; cd ..
```

```
cd ~/bin
cp ffmpeg ffprobe ffplay ffmpegserver vsyasm x264 yasm ytasm /usr/local/bin
```

```
cd ~/ffmpeg_build/bin
cp lame x265 /usr/local/bin
echo "FFmpeg Compilation is Finished!"
```

...to here.

Concede permission of execution:

```
chmod +x /opt/ffmpeg.sh
```

Now be connected to Internet, run the script and wait about 30 minutes while the compilation:

```
cd /opt
```

```
./ffmpeg.sh
```

All the compiled files are installed in: /usr/local/bin

7)

----- Installation and configuration of MariaDB data server -----

MariaDB is the data server. Will install it. (Version 10.x):

```
sudo apt-get install mariadb-server
```

Run MariaDB:

```
/etc/init.d/mysql start
```

Now we give a root password to MariaDB. Please, replace `new-password` with your own:

```
mysqladmin -u root password new-password
```

Make a database with his own user for OpenMeetings:

```
mysql -u root -p
```

...will ask for the root password that you have just choosen, type it...

```
MariaDB [(none)]> CREATE DATABASE open332 DEFAULT CHARACTER SET 'utf8';
```

With this command we has created a database called open332.

Now we create an user on this database. User password must be of 8 digits minimum:

(Only one line with space between both)

```
MariaDB [(none)]> GRANT ALL PRIVILEGES ON open332.* TO 'hola'@'localhost'  
IDENTIFIED BY '1a2B3c4D' WITH GRANT OPTION;
```

- * `open332`is the database name.
- * `hola`is the user name for this database.
- * `1a2B3c4D` ..is the password for this user.

You can change the data...but remember it! Later we'll need it.

Now, we leave MariaDB:

```
MariaDB [(none)]> quit
```

8)

----- Installation of OpenMeetings -----

We'll install OpenMeetings in `/opt/red5332`. All the following information will be based on this directory.

Make the folder:

```
mkdir /opt/red5332
```



```
cd /opt/red5332
```

...and download the red5-OpenMeetings file:

```
wget http://apache.miloslavbrada.cz/openmeetings/3.3.2/bin/apache-openmeetings-3.3.2.zip
```

```
unzip apache-openmeetings-3.3.2.zip
```

...save the unloaded file to /opt:

```
mv apache-openmeetings-3.3.2.zip /opt
```

Do to **nobody** owner of the whole OpenMeetings folder installation, by security:

```
chown -R nobody /opt/red5332
```

Download and install the connector between OpenMeetings and MariaDB:

```
cd /opt
```

(Only one line without space between both)

```
wget http://repo1.maven.org/maven2/mysql/mysql-connector-java/5.1.42/mysql-connector-java-5.1.42.jar
```

...and copy it to where must be:

```
cp /opt/mysql-connector-java-5.1.42.jar /opt/red5332/webapps/openmeetings/WEB-INF/lib
```

Now we form OpenMeetings for our database in MariaDB:

```
gedit /opt/red5332/webapps/openmeetings/WEB-INF/classes/META-INF/mysql_persistence.xml
```

Modify line 72:

```
, Url=jdbc:mysql://localhost:3326/openmeetings_3_3?
```

...to

```
, Url=jdbc:mysql://localhost:3326/open332?
```

...it is the name of the database that we did initially.

If initially you choose another name for the database, please type it here. Save changes.

We protect the access to the file:

(Only one line without space between both)

```
chmod 640 /opt/red5332/webapps/openmeetings/WEB-INF/classes/META-INF/mysql_persistence.xml
```

9)

----- Script to launch red5-OpenMeetings -----

Please, download the red5 run script:

```
cd /opt
```

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/red5-ubdeb2
```

...and copy it to:

```
cp red5-ubdeb2 /etc/init.d/
```

...and concede permission of execution:

```
chmod +x /etc/init.d/red5-ubdeb2
```

10)

----- Run red5-OpenMeetings -----

Start MariaDB, if still it is not:

```
/etc/init.d/mysql start
```

...and now start red5-OpenMeetings. Please, be connected to Internet:

```
/etc/init.d/red5-ubdeb2 start
```

...will appear two text lines in the shell:

```
start-stop-daemon: --start needs --exec or --startas  
Try 'start-stop-daemon --help' for more information.
```

...you do nothing. Don't worry, everything work right,

...wait 40 seconds at least, in order that red5 it is runing completely. And after this, can go to:

<http://localhost:5080/openmeetings/install>

...there will appear a page similar to this one:

OpenMeetings

1. Enabling import of PDFs into whiteboard

- Install **GhostScript** on the server, you can get more information on <http://pages.cs.wisc.edu/~ghost/> regarding installation. The instructions for installation can be found there, however on most linux systems you can get it via your favorite package managers (apt-get it).
- Install **SWFTools** on the server, you can get more information on <http://www.swftools.org/> regarding installation. Some of the Linux distributions already have it in there package manager see <http://packages.debian.org/unstable/utils/swftools>, the recommended version of **SWFTools** is 0.9 as prior version have a bug that does lead to wrong object dimensions in the Whiteboard

If you have further questions or need support in installation or hosting:

Community-Support:

[Mailing lists](#)

Commercial-Support:

[Commercial-Support](#)

<
>
>>
Finish

...press on > button (bottom), and will show the default database configuration

with Derby, but we employ MySQL (MariaDB),

OpenMeetings

DB configuration

Recommendation for production environment

By default OpenMeetings uses the integrated [Apache Derby](#) database. For production environment you should consider using [MySQL](#), [PostgreSQL](#), [IBM DB2](#), [MSSQL](#) or [Oracle](#)

NOTE Please use unpredictable DB login and 'strong' password with length 8 characters or more.

Choose DB type

Specify the name of the database

Check

<
>
>>
Finish

...then, scroll and **Choose DB type** to MySQL:

OpenMeetings

DB configuration

Recommendation for production environment

By default OpenMeetings uses the integrated Apache Derby database. For production environment you should consider using MySQL, PostgreSQL, IBM DB2, MSSQL or Oracle

NOTE Please use unpredictable DB login and 'strong' password with length 8 characters or more.

Choose DB type	<input type="text" value="MySQL"/>
Specify DB host	<input type="text" value="localhost"/>
Specify DB port	<input type="text" value="3306"/>
Specify the name of the database	<input type="text" value="open332"/>
Specify DB user	<input type="text"/>
Specify DB password	<input type="text"/>

...will show the database configuration we made in step 8. If you`ve choose any other different name for this, will show equally.

Now we must introduce the user name we did for our data base, at the step 7, and his password:

Specify DB user = **hola**

Specify DB password = **1a2B3c4D**

Please, press button, and will go to:

OpenMeetings

Userdata

Username	<input type="text"/>
Userpass	<input type="text"/>
E-Mail	<input type="text"/>
User Time Zone	<input type="text" value="Europe/Madrid"/>

Group(Domains)

Name	<input type="text"/>
------	----------------------

Here, we must introduce a user name for OpenMeetings, and his password. This must have 8 digits minimum, and at least 1 special symbol like: +(%#!...etc.


Username = a-name ...this user will be administrator.

Userpass = password ...for the previous user.

Email = email-adress ...of the previous user.

User Time Zone = country where is this server.

Name = example-openmeetings ...group name to choose.

Press the button  and will lead us to a new page (below) where you can select the language for your OpenMeetings server, as well as other options such as the configuration of the mail server being used to send invitations or meetings from OpenMeetings:

OpenMeetings

Configuration

Allow self-registering (allow_frontend_register)	Yes <input type="button" value="v"/>
Send Email to new registered Users (sendEmailAtRegister)	No <input type="button" value="v"/>
New Users need to verify their EMail (sendEmailWithVerificationCode)	No <input type="button" value="v"/>
Default Rooms of all types will be created	Yes <input type="button" value="v"/>
Mail-Referer (system_email_addr)	noreply@openmeetings.apache.org
SMTP-Server (smtp_server)	localhost
SMTP-Server Port(default SmtP-Server Port is 25) (smtp_port)	25
SMTP-Username (email_username)	<input type="text"/>
SMTP-Userpass (email_userpass)	<input type="text"/>
Enable TLS in Mail Server Auth	No <input type="button" value="v"/>
Set inviter's email address as ReplyTo in email invitations (inviter.email.as.replyto)	Yes <input type="button" value="v"/>
Default Language	inglés <input type="button" value="v"/>
Default Font for Export [default_export_font]	TimesNewRoman <input type="button" value="v"/>


A valid example to configure the mail server with Gmail, is as follows:
(replace **john@gmail.com** with your real Gmail account)


Mail-Refer (system_email_addr)	==	john@gmail.com
SMTP-Server (smtp_server)	==	smtp.gmail.com
SMTP-Server Port (default Smtip-Server Port is 25) (smtp_port)	==	587
SMTP-Username (email_username)	==	john@gmail.com
SMTP-Userpass (email_userpass)	==	password of john@gmail.com
Enable TLS in Mail Server Auth	==	Yes

To select the language of your server OpenMeetings, please scroll on the line:

Default Language == english

...the rest can leave as is.

Now press the button  and a new page will appear:



OpenMeetings

Converters

SWFTools Zoom ⓘ	<input type="text" value="100"/>	
SWFTools JPEG Quality ⓘ	<input type="text" value="85"/>	
SWFTools Path ⓘ	<input type="text"/>	Check
ImageMagick Path ⓘ	<input type="text"/>	Check
FFMPEG Path ⓘ	<input type="text"/>	Check
SoX Path ⓘ	<input type="text"/>	Check
OpenOffice/LibreOffice Path for jodconverter ⓘ	<input type="text"/>	Check

see also [Installation](#)

< > >> Finish

Here we'll introduce the respective paths for the image, video, audio and conversion of uploaded files:

SWFTools Path == /usr/bin


ImageMagick Path == /usr/bin

FFMPEG Path == /usr/local/bin

SOX Path == /usr/local/bin

OpenOffice/LibreOffice Path for jodconverter == /usr/lib/libreoffice (32 bits - 64bits)

As you go introducing paths, you can check if they are correct by pressing the button labeled **Check**. If it does not display any error message, that is OK.

Once completed the paths, please click the button  and move on to another page that would be to activate the SIP. We will leave it as is, unless you want to activate it knowing what it does:

OpenMeetings

Crypt Type

Crypt Class

You can use this default crypt type which is equal to PHP-MD5 function or BSD-Style encryption by using: **org.apache.openmeetings.util.crypt.MD5CryptImplementation** for more information or to write your own Crypt-Style see: [Custom Crypt Mechanism](#) You can edit this value later BUT previous created Users and Sessions might be not usable anymore

red5SIP Configuration

Enable SIP

Enable red5SIP integration


SIP rooms prefix

Prefix for phone number of conference rooms

SIP extensions context

Context of Asterisk extensions

Now push the button  and will show this window:




Press **Finish** button ...wait a seconds untill the tables are fill in the database.

When has concluded, this another page will appear. **Don't** clic on [Enter the Application](#).

First is need it to restart the server. Please, be connected to Internet:


[/etc/init.d/red5-ubdeb2 restart](#)



Now yes, you can clic on [Enter the Application](#), or go with your browser to:

<http://localhost:5080/openmeetings>

...and will take us to the entry of OpenMeetings:



The screenshot shows a login window titled "Login". It contains the following elements:

- Username or mail address: [text input field]
- Password: [password input field]
- Remember login
- [Forgotten your password?](#)
- [Network testing](#)
- Buttons: "Not a member?" and "Sign in"

Introduce the user's name and the password that you have chosen during the installation, push **Sign in** button, and...

...Congratulations!

The next time that you like accede to OpenMeetings would be:

<http://localhost:5080/openmeetings>

Remember to open in the server the two following ports:

1935 5080


...in order that it could accede to OpenMeetings from other machines in LAN or Internet.

11)


----- OpenMeetings's Configuration -----

Once you acced to OpenMeetings, if you would like to do any modification in the configuration, please go to:

Administration → Configuration



...and following the order of the red arrows:



Now we are going to remove files and folders that already do not serve us, if you do not prefer to save them:

```
rm -f /opt/mysql-connector-java-5.1.42.jar
```

```
rm -f /opt/sox-14.4.2.tar.gz
```

```
rm -f -R /opt/sox-14.4.2
```

And this is all.

If you have some doubt or question, please raise it in the Apache OpenMeetings forums:

<http://openmeetings.apache.org/mail-lists.html>



Thank you.

Alvaro Bustos