



Installation of Apache OpenMeetings 4.0.4 on Ubuntu 17.10

This tutorial is made based on a fresh installations of

ubuntu-mate-17.10-desktop-amd64.iso

It is tested with positive result. We will use the Apache's binary version OpenMeetings 4.0.4 stable, that is to say will suppress his compilation. It is done step by step.

25-5-2018

Starting...

1)

First, we update and upgrade the OS:

```
sudo apt-get update
```

```
sudo apt-get upgrade
```

2)

----- **Installation of OpenJava 1.8** -----

OpenMeetings **4.0.4** need Java **1.8** to work. So, we install OpenJava 1.8:

```
sudo apt install openjdk-8-jdk openjdk-8-jdk-headless
```

...and his plugin for web:

```
sudo apt install icedtea-8-plugin
```

Now, please, select OpenJava, if you have more than one java versions installed:

```
sudo update-alternatives --config java
```

To see the active java version:

```
java -version
```

3)

----- Installation of LibreOffice -----

LibreOffice is need it to convert to pdf the uploaded office files.

The ubuntu desktop iso have already LibreOffice installed.

We do it also for server iso:

```
sudo add-apt-repository ppa:libreoffice/ppa
```

```
sudo apt-get update
```

```
sudo apt-get install libreoffice
```

4)

----- Installation ImageMagick and Sox -----

ImageMagick, will work the image files, png, jpg, gif, etc. Will install it and some more libraries and paquets:

```
sudo apt-get install -y imagemagick libjpeg62 zlib1g-dev unzip make build-essential wget nmap
```

Sox, work the sound. We'll compile, because this version is newer than is in the repos:

```
cd /opt
```

```
wget http://sourceforge.net/projects/sox/files/sox/14.4.2/sox-14.4.2.tar.gz
```

```
tar xzvf sox-14.4.2.tar.gz
```

```
cd /opt/sox-14.4.2
```

```
./configure
```

```
make && make install
```

5)

----- **Installation of Adobe Flash Player** -----

OpenMeetings even need Adobe Flash Player for cam and audio. We install it

```
sudo apt-get install flashplugin-installer
```

6)

----- **Compilation of FFmpeg** -----

FFmpeg will work with video. This compilation is based on:

<https://trac.ffmpeg.org/wiki/CompilationGuide/Ubuntu>

Updated files to 25-5-2018. Install some libraries:

(Only one line with space between each one)

```
sudo apt-get -y --force-yes install autoconf automake build-essential libass-dev libfreetype6-dev  
libgpac-dev libsd1.2-dev libtheora-dev libtool libva-dev libvdpau-dev libvorbis-dev libxcb1-dev  
libxcb-shm0-dev libxcb-xfixes0-dev pkg-config texi2html zlib1g-dev nasm libx264-dev cmake  
mercurial libopus-dev curl git vlc
```

I made a script that will download, compile and install ffmpeg.
The result of any recording we do in OpenMeetings, will be in mp4 format.
Please, download the script:

```
cd /opt
```

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/ffmpeg_UbunDebi.sh
```

...concede permission of execution:

```
chmod +x ffmpeg_UbunDebi.sh
```

...and run it (be connected to Internet). The compilation will spend about 20-30 minutes:

```
./ffmpeg_UbunDebi.sh
```

When finish the compilation, a text will announce it:

FFmpeg Compilation is Finished!

...then, please, go to **step 7**).

7)

----- Installation and configuration of MariaDB data server -----

MariaDB is the data server. Will install it. (Version 10.x):

```
sudo apt-get install mariadb-server
```

Run MariaDB:

```
/etc/init.d/mysql start
```

Now we give a root password to MariaDB. Please, replace **new-password** with your own:

```
mysqladmin -u root password new-password
```

Make a database with his own user for OpenMeetings:

```
mysql -u root -p
```

...will ask for the root password that you have just chosen, type it...

```
MariaDB [(none)]> CREATE DATABASE open404 DEFAULT CHARACTER SET 'utf8';
```

With this command we has created a database called open404.

Now we create an user on this database. User password must be of 8 digits minimum:

(Only one line with space between both)

```
MariaDB [(none)]> GRANT ALL PRIVILEGES ON open404.* TO 'hola'@'localhost'  
IDENTIFIED BY '1a2B3c4D' WITH GRANT OPTION;
```

- * **open404**is the database name.
- * **hola**is the user name for this database.
- * **1a2B3c4D** ..is the password for this user.

You can change the data...but remember it! Later we'll need it.

Now, we leave MariaDB:

```
MariaDB [(none)]> quit
```

8)

----- Installation of OpenMeetings -----

We'll install OpenMeetings in /opt/red5404. All the following information will be based on this directory.

Make the folder:

```
mkdir /opt/red5404
```

```
cd /opt/red5404
```

...and download the red5-OpenMeetings file:

```
wget http://archive.apache.org/dist/openmeetings/4.0.4/bin/apache-openmeetings-4.0.4.zip
```

```
unzip apache-openmeetings-4.0.4.zip
```

...save the unloaded file to /opt:

```
mv apache-openmeetings-4.0.4.zip /opt
```

Do to **nobody** owner of the whole OpenMeetings folder installation, by security:

```
chown -R nobody /opt/red5404
```

Download and install the connector between OpenMeetings and MariaDB:

```
cd /opt
```

(Only one line without space between both)

```
wget http://repo1.maven.org/maven2/mysql/mysql-connector-java/5.1.46/mysql-connector-java-5.1.46.jar
```

...and copy it to where must be:

```
cp /opt/mysql-connector-java-5.1.46.jar /opt/red5404/webapps/openmeetings/WEB-INF/lib
```

9)

----- Script to launch red5-OpenMeetings -----

Please, download the red5 run script:

```
cd /opt
```

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/red5-ubdeb2
```

...and copy it to:

```
cp red5-ubdeb2 /etc/init.d/
```

...and concede permission of execution:

```
chmod +x /etc/init.d/red5-ubdeb2
```

10)

----- **Run red5-OpenMeetings** -----

Start MariaDB, if still it is not:

```
/etc/init.d/mysql start
```

...and now start red5-OpenMeetings. Please, be connected to Internet:

```
/etc/init.d/red5-ubdeb2 start
```

...will appear two text lines in the shell:

```
start-stop-daemon: --start needs --exec or --startas
Try 'start-stop-daemon --help' for more information.
```

...you do nothing. Don't worry, everything work right,

...wait 40 seconds at least, in order that red5 it is runing completely. And after this, can go to:

<http://localhost:5080/openmeetings/install>

...there will appear a page similar to this one:

OpenMeetings

1. Enabling import of PDFs into whiteboard

- Install **GhostScript** on the server, you can get more information on <http://pages.cs.wisc.edu/~ghost/> regarding installation. The instructions for installation can be found there, however on most linux systems you can get it via your favorite package managers (apt-get it).

If you have further questions or need support in installation or hosting:


Community-Support:


[Mailing lists](#)

Commercial-Support:

[Commercial-Support](#)

< > >> Finish

...press on  button (bottom), and will show the default database configuration with Derby, but we employ MySQL (MariaDB),



OpenMeetings

DB configuration

Recommendation for production environment


By default OpenMeetings uses the integrated Apache Derby database. For production environment you should consider using MySQL, PostgreSQL, IBM DB2, MSSQL or Oracle

NOTE Please use unpredictable DB login and 'strong' password with length 8 characters or more.

Choose DB type

Specify the name of the database

...then, scroll and **Choose DB type** to MySQL:



OpenMeetings

DB configuration

Recommendation for production environment

By default OpenMeetings uses the integrated Apache Derby database. For production environment you should consider using MySQL, PostgreSQL, IBM DB2, MSSQL or Oracle

NOTE Please use unpredictable DB login and 'strong' password with length 8 characters or more.

Choose DB type

Specify DB host

Specify DB port

Specify the name of the database

Specify DB user

Specify DB password


Now we must introduce the database name, user name and his password, we did at the step 7:

Specify the name of the database = open404

Specify DB user = hola

Specify DB password = 1a2B3c4D

...if you choose any other data, type it here.

Please, press  button, and will go to:



Here, we must introduce a user name for OpenMeetings, and his password. This must have 8 digits minimum, and at least 1 special symbol like: + (% # ! ...etc.


Username = a-name ...this user will be administrator.

Userpass = password ...for the previous user.

Email = email-adress ...of the previous user.

User Time Zone = country where is this server.

Name = example-openmeetings ...group name to choose.

Press the button  and will lead us to a new page (below) where you can select the language for your OpenMeetings server, as well as other options such as the configuration of the mail server being used to send invitations or meetings from OpenMeetings:

OpenMeetings

Configuration

Allow self-registering	<input checked="" type="checkbox"/>
Send Email to new registered Users	<input type="checkbox"/>
New Users need to verify their EMail	<input type="checkbox"/>
Default DB objects of all types will be created (including Rooms, OAuth2 servers etc.)	<input checked="" type="checkbox"/>
Mail-Referer	<input type="text" value="noreply@openmeetings.apache.org"/>
SMTP-Server	<input type="text" value="localhost"/>
SMTP-Server Port(default SmtP-Server Port is 25)	<input type="text" value="25"/>
SMTP-Username	<input type="text"/>
SMTP-Userpass	<input type="text"/>
Enable TLS in Mail Server Auth	<input type="checkbox"/>
Set inviter's email address as ReplyTo in email invitations	<input checked="" type="checkbox"/>
Default Language	<input type="text" value="inglés"/>

A valid example to configure the mail server with Gmail, is as follows:
(replace **john@gmail.com** with your real Gmail account)







Mail-Refer	==	john@gmail.com
SMTP-Server	==	smtp.gmail.com
SMTP-Server Port (default SmtP-Server Port is 25)	==	587
SMTP-Username	==	john@gmail.com
SMTP-Userpass	==	password of john@gmail.com
Enable TLS in Mail Server Auth	==	...turn green the button to activate
Default Language	==	...select your language

...the rest you can change it as you like.

Now press the button  and a new page will appear:

OpenMeetings

Converters

Document conversion DPI 	<input style="width: 90%;" type="text" value="150"/>	
Document conversion JPEG Quality 	<input style="width: 90%;" type="text" value="90"/>	
ImageMagick Path 	<input style="width: 90%;" type="text"/>	<input type="button" value="Check"/>
FFMPEG Path 	<input style="width: 90%;" type="text"/>	<input type="button" value="Check"/>
SoX Path 	<input style="width: 90%;" type="text"/>	<input type="button" value="Check"/>
OpenOffice/LibreOffice Path for jodconverter 	<input style="width: 90%;" type="text"/>	<input type="button" value="Check"/>

see also [Installation](#)

Here we'll introduce the respective paths for the image, video, audio and conversion of uploaded files:


ImageMagick Path == `/usr/bin`

FFMPEG Path == `/usr/local/bin`

SOX Path == `/usr/local/bin`

OpenOffice/LibreOffice Path for jodconverter == `/usr/lib/libreoffice (32bit - 64bit)`

As you go introducing paths, you can check if they are correct by pressing the button labeled **Check**. If it does not display any error message, that is OK.

Once completed the paths, please click the button  and move on to another page that would be to activate the SIP. We will leave it as is, unless you want to activate it knowing what it does:

The screenshot shows a configuration window titled "OpenMeetings". It has two main sections:

- Crypt Type**: Contains a "Crypt Class" field with the value "org.apache.openmeetings.util.crypt.SCr".
- red5SIP Configuration**: Contains three fields:
 - "Enable SIP" with a red toggle switch.
 - "SIP rooms prefix" with the value "400".
 - "SIP extensions context" with the value "rooms".

At the bottom right, there are four buttons: "<", ">", ">>", and "Finish".

Now push the button  and will show this window:

The screenshot shows the "OpenMeetings" window after clicking the right arrow button. The main area contains the text "Please click 'Finish' button to start installation!" and a large empty text input field. At the bottom right, there are four buttons: "<", ">", ">>", and "Finish".

Press **Finish** button ...wait a seconds untill the tables are fill in the database.

When has concluded, this another page will appear. **Don't** clic on [Enter the Application](#).

First is need it to restart the server. Please, be connected to Internet:

[/etc/init.d/red5-ubdeb2 restart](#)

OpenMeetings

[Enter the Application](#)

Database was changed, please restart application to avoid possible issues

If your Red5-Server runs on a different Port or on a different domain
alter the config values of the client

Mailing list
<http://openmeetings.apache.org/mail-lists.html>

There are some companies that also offer commercial support for Apache OpenMeetings:
<http://openmeetings.apache.org/commercial-support.html>

< > >> Finish

Now yes, you can clic on [Enter the Application](#), or go with your browser to:

<http://localhost:5080/openmeetings>

...and will take us to the entry of OpenMeetings:

Login

Username or mail address

Password

Remember login

[Forgotten your password?](#) [Network testing](#)

Not a member? Sign in

Introduce the user's name and the password that you have chosen during the installation, push **Sign in** button, and...

...**Congratulations!**

The next time that you like accede to OpenMeetings would be:

<http://localhost:5080/openmeetings>

Remember to open in the server the two following ports:

1935 5080


...in order that it could accede to OpenMeetings from other machines in LAN or Internet.

11)

----- **OpenMeetings's Configuration** -----

Once you acced to OpenMeetings, if you would like to do any modification in the configuration, please go to:

Administration → Configuration



...and following the order of the red arrows:

Home Rooms Recordings Administration

50 Search

ID	Key	Value
1	crypt.class.name	org.apache.openmeetings.util.crypt.SCryptImplementation
2	allow.frontend.register	true
3	allow.soap.register	true
4	allow.oauth.register	true
5	default.group.id	1
6	mail.smtp.server	localhost
7	mail.smtp.port	25
8	mail.smtp.system.email	noreply@openmeetings.apache.org
9	mail.smtp.user	
10	mail.smtp.pass	
11	mail.smtp.starttls.enable	false
12	mail.smtp.connection.timeout	30000
13	mail.smtp.timeout	30000
14	application.name	OpenMeetings
15	default.lang.id	8
16	document.dpi	150
17	document.quality	90
18	path.imagemagick	
19	path.sox	
20	path.ffmpeg	
21	path.office	
22	dashboard.rss.feed1	http://mail-archives.apache.org/mod_mbox/openmeetings-user/?format=atom
23	dashboard.rss.feed2	http://mail-archives.apache.org/mod_mbox/openmeetings-dev/?format=atom
24	send.email.at.register	false
25	send.email.with.verification	false

Configuration

Type: string

Key: path.ffmpeg

Value:

Last update: Oct 17, 2017 5:54:57 PM

Updated by: toro

Comment: Path To FFMPEG

1 2 3

Chat

And this is all.

If you have some doubt or question, please raise it in the Apache OpenMeetings forums:

<http://openmeetings.apache.org/mail-lists.html>



Thank you.

Alvaro Bustos