



## Installation of Apache OpenMeetings 4.0.8 on Ubuntu 16.04 LTS

The present tutorial is made based on a fresh installations of

**ubuntu-mate-16.04-desktop-amd64.iso**

It is tested with positive result. We will use the Apache's binary version OpenMeetings 4.0.8 stable, that is to say will suppress his compilation. It is done step by step.

8-3-2019

Starting...

1)

First, we update and upgrade the OS:

```
sudo apt-get update
```

```
sudo apt-get upgrade
```

2)

----- **Installation of OpenJava 1.8** -----

OpenMeetings **4.0.8** need Java **1.8** to work. So, we install OpenJava 1.8:

```
sudo apt install openjdk-8-jdk openjdk-8-jdk-headless
```

...and his plugin for web:

```
sudo apt install icedtea-8-plugin icedtea-netx
```

Now, please, select OpenJava 8, if you have more than one java versions installed:

```
sudo update-alternatives --config java
```

To see the active java version:

```
java -version
```

3)

#### ----- Installation of LibreOffice -----

LibreOffice is need it to convert to pdf the uploaded office files.

The ubuntu desktop iso have already LibreOffice installed, but we do also for server iso:

```
sudo add-apt-repository ppa:libreoffice/ppa
```

```
sudo apt-get update
```

```
sudo apt-get install libreoffice
```

Now some kind of information only:

LibreOffice installation folder is /usr/lib/libreoffice.

4)

#### ----- Installation ImageMagick and Sox -----

**ImageMagick**, will work the image files, png, jpg, gif, etc. Will install it and some more libraries and paquets:

```
sudo apt-get install -y imagemagick libjpeg62 zlib1g-dev unzip make build-essential wget nmap
```

**Sox**, work the sound. We'll compile, because this version is newer than the repo:

```
cd /opt
```

```
wget http://sourceforge.net/projects/sox/files/sox/14.4.2/sox-14.4.2.tar.gz
```

```
tar xzvf sox-14.4.2.tar.gz
```

```
cd /opt/sox-14.4.2
```

```
./configure
```

```
make && make install
```

5)

----- **Installation of Adobe flash player** -----

OpenMeetings even need Adobe Flash Player for cam and audio. We install it

```
sudo apt-get install flashplugin-installer
```

6)

----- **Compilation of FFmpeg** -----

**FFmpeg** will work with video.

This compilation is based on:

<https://trac.ffmpeg.org/wiki/CompilationGuide/Ubuntu>

Updated files to 8-3-2019. Install some libraries:

(Only one line with space between each one)

```
sudo apt-get -y --force-yes install autoconf automake build-essential libass-dev libfreetype6-dev  
libgpgac-dev libsdl1.2-dev libtheora-dev libtool libva-dev libvdpau-dev libvorbis-dev libxcb1-dev  
libxcb-shm0-dev libxcb-xfixes0-dev pkg-config texi2html zlib1g-dev nasm libx264-dev cmake  
mercurial libopus-dev curl git vlc
```

I made a script that will download, compile and install ffmpeg.

The result of any recording we do in OpenMeetings, will be in mp4 format.

Please, download the script:

```
cd /opt
```

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/ffmpeg-ubuntu.sh
```

...concede permission of execution:

```
chmod +x ffmpeg-ubuntu.sh
```

...and run it (be connected to Internet). The compilation will spend about 20-30 minutes:

`./ffmpeg-ubuntu.sh`

When finish the compilation, a text will announce it:

**FFmpeg Compilation is Finished!**

Then, please, go to **step 7)**.

All the compiled files are installed in: `/usr/local/bin`

7)

----- **Installation and configuration of MariaDB data server** -----

**MariaDB** is the data server. Will install it. (Version 10.x):

`sudo apt-get install mariadb-server`

Run MariaDB:

`/etc/init.d/mysql start`

Now we give a root password to MariaDB. Please, replace **new-password** with your own:

`mysqladmin -u root password new-password`

Make a database with his own user for OpenMeetings:

`mysql -u root -p`

...will ask for the root password that you have just chosen, type it...

MariaDB [(none)]> **CREATE DATABASE open408 DEFAULT CHARACTER SET 'utf8';**

With this command we has created a database called open408.

Now we create an user on this database. User password must be of 8 digits minimum:

(Only one line with space between both)

MariaDB [(none)]> **GRANT ALL PRIVILEGES ON open408.\* TO 'hola'@'localhost' IDENTIFIED BY '1a2B3c4D' WITH GRANT OPTION;**

- \* **open408** .....is the database name.
- \* **hola** .....is the user name for this database.
- \* **1a2B3c4D** ..is the password for this user.

You can change the data...but remember it! Later we'll need it.

Now, we leave MariaDB:

```
MariaDB [(none)]> quit
```

8)

### ----- Installation of OpenMeetings -----

We'll install OpenMeetings in /opt/red5408. All the following information will be based on this directory.

Make the folder:

```
mkdir /opt/red5408
```

```
cd /opt/red5408
```

...and download the red5-OpenMeetings file:

```
wget http://archive.apache.org/dist/openmeetings/4.0.8/bin/apache-openmeetings-4.0.8.zip
```

```
unzip apache-openmeetings-4.0.8.zip
```

...save the unloaded file to /opt:

```
mv apache-openmeetings-4.0.8.zip /opt
```

Do to **nobody** owner of the whole OpenMeetings folder installation, by security:

```
chown -R nobody /opt/red5408
```

Download and install the connector between OpenMeetings and MariaDB:

```
cd /opt
```

(Only one line without space between both)

```
wget http://repo1.maven.org/maven2/mysql/mysql-connector-java/5.1.47/mysql-connector-java-5.1.47.jar
```

...and copy it to where must be:

```
cp /opt/mysql-connector-java-5.1.47.jar /opt/red5408/webapps/openmeetings/WEB-INF/lib
```

9)

----- Script to launch red5-OpenMeetings -----

Please, download the red5 run script:

```
cd /opt
```

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/red5-ubdeb2
```

...and copy it to:

```
cp red5-ubdeb2 /etc/init.d/
```

...and concede permission of execution:

```
chmod +x /etc/init.d/red5-ubdeb2
```

10)

----- Run red5-OpenMeetings -----

Start MariaDB, if still it is not:

```
/etc/init.d/mysql start
```

...and now start red5-OpenMeetings. Please, be connected to Internet:

```
/etc/init.d/red5-ubdeb2 start
```

...will appear two text lines in the shell:

```
start-stop-daemon: --start needs --exec or --startas  
Try 'start-stop-daemon --help' for more information.
```

...you do nothing. Don't worry, everything work right,

...wait 40 seconds at least, in order that red5 it is runing completely. And after this, can go to:

<http://localhost:5080/openmeetings/install>

...there will appear a page similar to this one:

### OpenMeetings

**1. Enabling import of PDFs into whiteboard**


- Install **GhostScript** on the server, you can get more information on <http://pages.cs.wisc.edu/~ghost/> regarding installation. The instructions for installation can be found there, however on most linux systems you can get it via your favorite package managers (apt-get it).

**If you have further questions or need support in installation or hosting:**

**Community-Support:**  
[Mailing lists](#)

**Commercial-Support:**  
[Commercial-Support](#)

< > >> Finish

...press on  button (bottom), and will show the default database configuration with Derby, but we employ MySQL (MariaDB),

### OpenMeetings

**DB configuration**

**Recommendation for production environment**

By default OpenMeetings uses the integrated [Apache Derby](#) database. For production environment you should consider using [MySQL](#), [PostgreSQL](#), [IBM DB2](#), [MSSQL](#) or [Oracle](#)

**NOTE** Please use unpredictable DB login and 'strong' password with length 8 characters or more.

Choose DB type

Specify the name of the database

Check

< > >> Finish

...then, scroll and **Choose DB type** to MySQL:

**OpenMeetings**

**DB configuration**

**Recommendation for production environment**

By default OpenMeetings uses the integrated [Apache Derby](#) database. For production environment you should consider using [MySQL](#), [PostgreSQL](#), [IBM DB2](#), [MSSQL](#) or [Oracle](#)

**NOTE** Please use unpredictable DB login and 'strong' password with length 8 characters or more.

Choose DB type	<input type="text" value="MySQL"/>
Specify DB host	<input type="text" value="localhost"/>
Specify DB port	<input type="text" value="3306"/>
Specify the name of the database	<input type="text" value="openmeetings"/>
Specify DB user	<input type="text"/>
Specify DB password	<input type="password"/>

Now we must introduce the database name, user name and password, we did at the step 7:

**Specify the name of the database = open408**

**Specify DB user = hola**

**Specify DB password = 1a2B3c4D**

...if you choose a different data, type it here.

Please, press  button, and will go to:

**OpenMeetings**

**Userdata**

Username	<input type="text"/>
Userpass	<input type="password"/>
E-Mail	<input type="text"/>
User Time Zone	<input type="text" value="Europe/Madrid"/>

**Group(Domains)**

Name	<input type="text"/>
------	----------------------



Here, we must introduce a user name for OpenMeetings, and his password. This must have 8 digits minimum, and at least 1 special symbol like: + ( % # ! ...etc.


**Username** = a-name ...this user will be administrator.

**Userpass** = password ...for the previous user.

**Email** = email-adress ...of the previous user.

**User Time Zone** = country where is this server.

**Name** = example-openmeetings ...group name to choose.

Press the button  and will lead us to a new page (below) where you can select the language for your OpenMeetings server, as well as other options such as the configuration of the mail server being used to send invitations or meetings from OpenMeetings:

**OpenMeetings**

**Configuration**

Allow self-registering	<input checked="" type="checkbox"/>
Send Email to new registered Users	<input type="checkbox"/>
New Users need to verify their EMail	<input type="checkbox"/>
Default DB objects of all types will be created (including Rooms, OAuth2 servers etc.)	<input checked="" type="checkbox"/>
Mail-Referer	<input type="text" value="noreply@openmeetings.apache.org"/>
SMTP-Server	<input type="text" value="localhost"/>
SMTP-Server Port(default SmtP-Server Port is 25)	<input type="text" value="25"/>
SMTP-Username	<input type="text"/>
SMTP-Userpass	<input type="text"/>
Enable TLS in Mail Server Auth	<input type="checkbox"/>
Set inviter's email address as ReplyTo in email invitations	<input checked="" type="checkbox"/>
Default Language	<input type="text" value="inglés"/>

A valid example to configure the mail server with Gmail, is as follows:  
(replace **john@gmail.com** with your real Gmail account)

<b>Mail-Refer</b>	==	john@gmail.com
<b>SMTP-Server</b>	==	smtp.gmail.com
<b>SMTP-Server Port (default Smtplib-Server Port is 25)</b>	==	587
<b>SMTP-Username</b>	==	john@gmail.com
<b>SMTP-Userpass</b>	==	password of john@gmail.com
<b>Enable TLS in Mail Server Auth</b>	==	...turn green the button to activate
<b>Default Language</b>	==	...select your language

...the rest you can change it as you like.

Now press the button  and a new page will appear:

**OpenMeetings**

**Converters**

Document conversion DPI ⓘ

Document conversion JPEG Quality ⓘ

ImageMagick Path ⓘ

FFMPEG Path ⓘ

SoX Path ⓘ

OpenOffice/LibreOffice Path for jodconverter ⓘ

*see also [Installation](#)*

Here we'll introduce the respective paths for the image, video, audio and conversion of uploaded files:


**ImageMagick Path** == /usr/bin


**FFMPEG Path** == /usr/local/bin

**SOX Path** == /usr/local/bin

**OpenOffice/LibreOffice Path for jodconverter** == /usr/lib/libreoffice (32 bits - 64bits)


As you go introducing paths, you can check if they are correct by pressing the button labeled **Check**. If it does not display any error message, that is OK.

Once completed the paths, please click the button  and move on to another page that would be to activate the SIP. We will leave it as is, unless you want to activate it knowing what it does:



The screenshot shows the 'OpenMeetings' configuration window. It has two main sections: 'Crypt Type' and 'red5SIP Configuration'. In the 'Crypt Type' section, the 'Crypt Class' is set to 'org.apache.openmeetings.util.crypt.SCr'. In the 'red5SIP Configuration' section, 'Enable SIP' is checked (indicated by a red square), 'SIP rooms prefix' is set to '400', and 'SIP extensions context' is set to 'rooms'. At the bottom right, there are navigation buttons: '<', '>', '>>', and 'Finish'.

Now push the button  and will show this window:



The screenshot shows the 'OpenMeetings' configuration window after clicking the next button. The window displays the message 'Please click "Finish" button to start installation!' above a large empty text input field. At the bottom right, there are navigation buttons: '<', '>', '>>', and 'Finish'.

Press **Finish** button ...wait a seconds until the tables are fill in the database.

When has concluded, this another page will appear. **Don't** clic on [Enter the Application](#).

First is need it to restart the server. Please, be connected to Internet:

`/etc/init.d/red5-ubdeb2 restart`

**OpenMeetings**

[Enter the Application](#)

Database was changed, please restart application to avoid possible issues

If your Red5-Server runs on a different Port or on a different domain  
alter the config values of the client

**Mailing list**

<http://openmeetings.apache.org/mail-lists.html>

**There are some companies that also offer commercial support for Apache OpenMeetings:**

<http://openmeetings.apache.org/commercial-support.html>

< > >> Finish

Now yes, you can clic on [Enter the Application](#), or go with your browser to:

<http://localhost:5080/openmeetings>

...and will take us to the entry of OpenMeetings:

**Login**

Username or mail address

Password

Remember login

[Forgotten your password?](#) [Network testing](#)

Not a member? Sign in

Introduce the user's name and the password that you have chosen during the installation, push **Sign in** button, and...

...**Congratulations!**

The next time that you like accede to OpenMeetings would be:

<http://localhost:5080/openmeetings>

Remember to open in the server the two following ports:

**1935 5080**


...in order that it could accede to OpenMeetings from other machines in LAN or Internet.

11)

----- **OpenMeetings's Configuration** -----

Once you acced to OpenMeetings, if you would like to do any modification in the configuration, please go to:

**Administration → Configuration**



The screenshot displays the OpenMeetings user interface. At the top, there is a navigation bar with four items: "Home", "Rooms", "Recordings", and "Administration". The "Administration" item is highlighted with a red arrow pointing upwards. Below the navigation bar, there is a "Welcome" section with a user profile card. The profile card includes a placeholder image with a question mark, the text "Hello firstname lastname", the time zone "Europe/Madrid", "Unread messages 0", and a link to "Edit your profile". There is also a button labeled "Upload new image". At the bottom of the page, there is a section titled "Help and support".

...and following the order of the red arrows:

The screenshot shows the OpenMeetings Administration interface. On the left is a table of configuration items. On the right is a 'Configuration' details panel for the selected item 'path.ffmpeg'. Three red arrows indicate the sequence of actions: arrow 1 points to the 'path.ffmpeg' row in the table; arrow 2 points to the 'Value' input field in the details panel; arrow 3 points to the 'Save' button (represented by a floppy disk icon) in the top right of the details panel.

ID	Key	Value
1	crypt.class.name	org.apache.openmeetings.util.crypt.SCryptImplementation
2	allow.frontend.register	true
3	allow.soap.register	true
4	allow.oauth.register	true
5	default.group.id	1
6	mail.smtp.server	localhost
7	mail.smtp.port	25
8	mail.smtp.system.email	noreply@openmeetings.apache.org
9	mail.smtp.user	
10	mail.smtp.pass	
11	mail.smtp.starttls.enable	false
12	mail.smtp.connection.timeout	30000
13	mail.smtp.timeout	30000
14	application.name	OpenMeetings
15	default.lang.id	8
16	document.dpi	150
17	document.quality	90
18	path.imagemagick	
19	path.sox	
20	path.ffmpeg	
21	path.office	
22	dashboard.rss.feed1	http://mail-archives.apache.org/mod_mbox/openmeetings-user/?format=atom
23	dashboard.rss.feed2	http://mail-archives.apache.org/mod_mbox/openmeetings-dev/?format=atom
24	send.email.at.register	false
25	send.email.with.verification	false

**Configuration Details for path.ffmpeg:**

- Type: string
- Key: path.ffmpeg
- Value:
- Last update: Oct 17, 2017 5:54:57 PM
- Updated by: toro
- Comment: Path To FFMPEG

12)

----- Special Step ImageMagick -----

We modify ImageMagick, so OpenMeetings can upload office files to whiteboard:

[nano /etc/ImageMagick-6/policy.xml](#)

...and comment out the two follow lines, near to bottom file:

```
<policy domain="coder" rights="none" pattern="PS" />  
<policy domain="coder" rights="none" pattern="PDF" />
```

...to:

```
<!-- <policy domain="coder" rights="none" pattern="PS" /> -->  
<!-- <policy domain="coder" rights="none" pattern="PDF" /> -->
```

Press in the keyboard **Ctrl+x**, will ask to save, press **Y**, and press **Enter** to exit nano editor.

This last must be repeated every time you update the system-ImageMagick.

-----

If you have some doubt or question, please raise it in the Apache OpenMeetings forums:

<http://openmeetings.apache.org/mailling-lists.html>



Also you can download if you like, a wallpaper of OpenMeetings for different devices such as:

PC, Mac, Smartphone, iPhone and Tablets. Here is the link to download:

[Download](#)

A DVD live iso with OpenMeetings 4.0.8 on Ubuntu 18.04 lts is at your disposal.

Can find it here:

[Live iso download](#)

Thank you.

Alvaro Bustos