



## Creating Let's Encrypt SSL Certificates and Installing Coturn on Debian 10 for OpenMeetings 6.3.0

This tutorial is basically made for those who have OpenMeetings 6.3.0 installed on your computer behind a NAT router. It's tested and working properly.

If you didn't have it installed, you can directly download the installation guide from here:

**[Download Installation OpenMeetings 6.3.0 on Debian 10](#)**

I thank Maxim Solodovnik and Carlos Heras, without whose collaboration in the trials practices could not have confirmed the proper functioning and thus be able to publish the present tutorial.

I also thank all those who have contributed such as Marcus Schulz and Daniel Baker. Thanks to all them.

Starting...

1)

----- Creating SSL Let's Encrypt certificates -----

Install certbot, needed to build the certificates:

```
su
```

```
apt install certbot
```

**It is important** that your pc-server does not have port 80 in use with some web server or some other. If so, stop it and continue with this step. When the certificates are completed, you can throw it again.

Let's Encrypt validate "SSL Certificate Authority (CA)" of your domain.

We'll run it with the --standalone parameter, so you can add each domain at the end requires a certificate, for exemple: -d newexemple.com

Change "exemple.com" to the true domain of your server:

```
certbot certonly --standalone -d exemple.com -d www.exemple.com
```

# You will be asked for an admin email address. Put a real one to get you keep you informed about certificates:

Installation succeeded.

Saving debug log to /var/log/letsencrypt/letsencrypt.log

Plugins selected: Authenticator standalone, Installer None

Enter email address (used for urgent renewal and security notices) (Enter 'c' to cancel): ...here your mail address and press **Enter**

# Ask if you agree:

```
-----  
Please read the Terms of Service at  
https://letsencrypt.org/documents/LE-SA-v1.2-November-15-2017.pdf. You must  
agree in order to register with the ACME server at  
https://acme-v02.api.letsencrypt.org/directory  
-----
```

(A)gree/(C)ancel: ...type... a ...and press **Enter**

# Ask if you want to share your email address:

```
-----  
Would you be willing to share your email address with the Electronic Frontier  
Foundation, a founding partner of the Let's Encrypt project and the non-profit  
organization that develops Certbot? We'd like to send you email about our work  
encrypting the web, EFF news, campaigns, and ways to support digital freedom.  
-----
```

(Y)es/(N)o: ...type... n ...and press **Enter**

when you finish making the certificates successfully, it will show the following:

IMPORTANT NOTES:

- **Congratulations!** Your certificate and chain have been saved at:  
/etc/letsencrypt/live/**your\_domain**/fullchain.pem  
Your key file has been saved at:  
/etc/letsencrypt/live/**your\_domain**/privkey.pem  
Your cert will expire on 2020-06-24. To obtain a new or tweaked version of this certificate in the future, simply run letsencrypt-auto again. To non-interactively renew *\*all\** of your certificates, run "letsencrypt-auto renew"
- If you like Certbot, please consider supporting our work by:

Donating to ISRG / Let's Encrypt: <https://letsencrypt.org/donate>  
Donating to EFF: <https://eff.org/donate-le>

2)

----- **Checking domain certificates** -----

We'll see where are stored the certificates we just create, that in our case will be at /etc/letsencrypt/live:

`ls /etc/letsencrypt/live`

...will show your domain name: **your\_domain**

All domains that you specified in the previous step will be located in the same certificate.

3)

----- **Renewing the SSL certificate** -----

The Let's Encrypt certificate has an drawback, and is that it is valid only 90 days, so we're going to have to renew it.

We can do this manually (always connected to Internet):

`certbot renew`

4)

----- **Configuring Tomcat-OpenMeetings with SSL certificates** -----

This configuration we will now make is only for the 5 or 6.x.x (not 4.x.x) openMeetings series. **This step number 4 must be repeated every 80 days**, after updating the certificates, as it is 90 Let's Encrypt's valid days.

I followed the OM installation path that show the OpenMeetings tutorials that are found on their official wiki site. I mean **/opt/open630**.

If you had done the installation on a different path, modify what you indicate below.

We already made the letsencrypt certificates for our domain in step 1.

Now let's create a PKCS12 that contains the full chain and the private one. It is necessary to have installed openssl. We install it if not:

```
apt install openssl
```

Now run the following command:

(Only one line with space between each of them)

```
openssl pkcs12 -export -out /tmp/example.com_fullchain_and_key.p12
-in /etc/letsencrypt/live/example.com/fullchain.pem
-inkey /etc/letsencrypt/live/example.com/privkey.pem -name tomcat
```

...replace **example.com** with your true domain (the same as when we made letsencrypt certificates)

...will ask for a password. Type one that you likes and paste in a text file (will need now)

And now convert that PKCS12 to JKS file using java keytool:

(Only one line with space between each of them)

```
keytool -importkeystore -deststorepass samplePassword -destkeypass samplePassword
-destkeystore /tmp/example.com.jks -srckeystore /tmp/example.com_fullchain_and_key.p12
-srstoretype PKCS12 -srcstorepass samplePassword -alias tomcat
```

...replace **example.com** with your true domain (twice), and **samplePassword** (three times) with the password you just choosed (it you pasted in a text file).

Copy the generated **example.com.jks** file to the Tomcat-OpenMeetings installation directory:

```
cp /tmp/example.com.jks /opt/open630/conf
```

...replace **example.com** with your true domain.

**# Configure Tomcat with the Java Keystore that we generated..**

For that edit server.xml file:

```
nano /opt/open630/conf/server.xml
```

...let's go to the block:

```
<Connector port="5443" protocol="org.apache.coyote.http11.Http11NioProtocol"
  maxThreads="150" SSLEnabled="true">
  <SSLHostConfig>
    <Certificate certificateKeystoreFile="conf/localhost.jks"
      certificateKeystorePassword="openmeetings"
      certificateKeystoreType="JKS"
      certificateVerification="false"
      sslProtocol="TLS"
      type="RSA" />
  </SSLHostConfig>
```

...and we modified it by leaving it like this:

```
<Connector port="5443" protocol="org.apache.coyote.http11.Http11NioProtocol"
  maxThreads="150" SSLEnabled="true">
  <SSLHostConfig>
    <Certificate certificateKeystoreFile="conf/example.com.jks"
      certificateKeystorePassword="samplePassword"
      certificateKeystoreType="JKS"
      certificateVerification="false"
      sslProtocol="TLS"
      type="RSA" />
  </SSLHostConfig>
```

...replace **example.com** with your true domain, and **samplePassword** with the password that you've just chosen (the one you just saved to a text file)

...exit the nano editor by pressing the **Ctrl+x** keys, ask if you save and press **Y** and then **Enter** to exit.

5)

#### ----- Coturn installation -----

Install Coturn (Turn server):

```
apt install coturn
```

...we edit the following file so that the Turn server can work:

```
nano /etc/default/coturn
```

...and we uncomment the line:

```
#TURNSEVER_ENABLED=1
```

....leaving it like this:

```
TURNSEVER_ENABLED=1
```

...exit the nano editor by pressing the **Ctrl+x** keys, ask if you save and press **Y** and then **Enter** to exit.

6)

#### ----- Setting of Turn server -----

Now we'll set up Turn. Created a folder where turn server store the logs:

```
mkdir -p /var/log/turnserver
```

...create a password that we'll need to put it in the configuration file of the turn server and later in an OpnMeetings file. We created it:

```
openssl rand -hex 32
```

...will generate something similar to this:

```
751c45cae60a2839711a94c8d6bf0089e78b2149ca602fdXXXXXXXXXXXXXXXXXXXX
```

...copy that long password and paste it into a text file by saving it.

Edit the turn configuration file:

```
nano /etc/turnserver.conf
```

...in this file we will have to uncomment (delete #) only the following lines:

```
use-auth-secret
```

```
static-auth-secret=751c45cae60a2839711a94c8d6bf0089e78b2149ca602fdXXXXXXXXXXXXXXXXXXXX
```

(on the above line put the long password we just saved in a text file)

`realm=your_real_domain` ...change company.org to your real domain

`stale-nonce=0` ...change 600 to 0 (zero)

`log-file=/var/log/turnserver/turnserver.log` .

(above change /var/log/turnserver.log to /var/log/turnserver/turnserver.log)

...exit the nano editor by pressing the **Ctrl+x** keys, ask if you save and press **Y** and then **Enter** to exit.

7)

### ----- Setting Up OpenMeetings 6.3.0 with Kurento media server-----

Edit the **openmeetings.properties** file of OpenMeetings:

`nano /opt/open630/webapps/openmeetings/WEB-INF/classes/openmeetings.properties`

...and in the `### Kurento ###` section we modify only the following lines:

```
#### Kurento ###
```

```
kurento.turn.url=
kurento.turn.user=
kurento.turn.secret=
```

...to

```
kurento.turn.url=Public IP of your server:3478
kurento.turn.user=
kurento.turn.secret=751c45cae60a2839711a94c8d6bf0089e78b2149ca602fdXXXXXXXXXXXXXXXXX
```

...above, in:

```
kurento.turn.secret=751c45cae60a2839711a94c8d6bf0089e78b2149ca602fdXXXXXXXXXXXXXXXXX
```

...replace the line: `751c45cae60a2839711a94c8d6bf0089e78b2149ca602fdXXXXXXXXXXXXXXXXX`

...by the long password that we generated in step 6 and that we save in a text file

Exit the nano editor by pressing the **Ctrl+x** keys, ask if you save and press **Y** and then **Enter** to exit.

Restart coturn: [/etc/init.d/coturn restart](#)

Restart docker: [/etc/init.d/docker restart](#)

Start Kurento: [docker start kms](#)

Tomcat-OpenMeetings: [/etc/init.d/tomcat34 restart](#)

8)

----- **Open ports required for servers**-----

We need open some ports in the router and the firewall for the servers access.

These are:

**3478 TCP-UDP IN**

**5443 TCP IN**

**8888 TCP IN**

**49152:65535 UDP IN-OUT**

...if you have installed on Ubuntu 18.04 gufw (ufw firewall interface) you can open them directly from there adding rules.

In case you prefer to open them (the firewall) with IPTables, these are the commands:

```
iptables -A INPUT -p tcp -m tcp --dport 3478 -j ACCEPT
```

```
iptables -A INPUT -p udp -m udp --dport 3478 -j ACCEPT
```

```
iptables -A INPUT -p tcp -m tcp --dport 5443 -j ACCEPT
```

```
iptables -A INPUT -p tcp -m tcp --dport 8888 -j ACCEPT
```

```
iptables -A INPUT -p udp --match multiport --dports 49152:65535 -j ACCEPT
```

```
iptables -A OUT -p udp --match multiport --dports 49152:65535 -j ACCEPT
```



...after launching the commands we save the changes:

```
service iptables save
```

...and restart IPTables:

```
service iptables restart
```

And with this we conclude.

-----

If you have some doubt or question, please raise it in the Apache OpenMeetings forums:

<https://openmeetings.apache.org/mailling-lists.html>

OpenMeetings



Thank you .

Alvaro Bustos (PMC and Committer at Apache OpenMeetings)