

**This Guide is intended to help users install and
configure Open Meetings 2.X**

**Parts of the guide have been updated from the
previous installation documentation from Alvaro
Bustos – greenes. -Thanks**

**This guide has been written step by step with
screenshots to aid in the successful build of OM.**


**SSL and Reverse proxy steps have been added
but are optional.**

Installing Debian (Minimal Headless System)


Step 1: - Base System




Choose 64 Bit install




Choose English




Choose "United Kingdom"




Choose "British English"




Set the hostname, in this case its “openmeetings”




Set your domain, in this case we have used “yourdomain.internal”




Set the root password.




Create new user for server (Non-priv)




Set password for new user




Use guided – entire disk




Select Disk to partition




Choose "All files in one partition"




Choose “Finish partitioning and write changes to disk”




And finally choose “yes”




Choose Debian archive – in this case we are using “United Kingdom”




Any archive will do closest to you; in this case we are using ftp.uk.debian.org




If you use a proxy server then add the details here, if you have full outbound access then just choose continue.




“apt” will now update the local repository information.




Choose not to participate in the survey.



Choose only SSH Server and Standard System utilities.



Choose Yes to install Grub.



Base install has now completed, choose continue to reboot into your new system.

Step 2: - Setup SSH Environment

```
Setting kernel variables ...done.
Configuring network interfaces...done.
Starting portmap daemon...
Starting NFS common utilities: statd.
Cleaning up temporary files...
Setting console screen modes.
Skipping font and keymap setup (handled by console-setup).
Setting up console font and keymap...done.
INIT: Entering runlevel: 2
Using makefile-style concurrent boot in runlevel 2.
Starting NFS common utilities: statd.
Starting portmap daemon...Already running..
Starting enhanced syslogd: rsyslogd.
Starting VirtualBox AdditionsVBoxService: 3.2.10_DSE r66523 started. Verbose level = 0
.
Starting ACPI services....
Starting deferred execution scheduler: atd.
Starting periodic command scheduler: cron.
Starting OpenBSD Secure Shell server: sshd.
Starting MTA: exim4.

Debian GNU/Linux 6.0 openmeetings tty1
openmeetings login: _
```

You should now be at the following screen, the next steps are easier done from a remote desktop using an SSH client such as putty. – But first we need to know our IP address, in most cases this was issued by your DHCP server (unless you specified manual network setup during install)

To find your IP address, first logon to your physical machine using root, then issue the following command:

ifconfig

This will show the following screen:

```
root@openmeetings:~# ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:22:1d:a1
          inet addr:10.17.23.3  Bcast:10.17.23.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:fe22:1da1/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:433 errors:0 dropped:0 overruns:0 frame:0
          TX packets:30 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:41590 (40.6 KiB)  TX bytes:2756 (2.6 KiB)


lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:8 errors:0 dropped:0 overruns:0 frame:0
          TX packets:8 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:560 (560.0 B)  TX bytes:560 (560.0 B)

root@openmeetings:~# _
```

You can see the IP Address in this case is 10.17.23.3 (Interface eth0)

You can now log off of the server.


From your desktop machine open your SSH client, in this case we will be using the putty client to connect to our new Server.




Enter the details and choose open



The first log on you will receive this message; you can choose yes here and accept the key.





```

# deb http://security.debian.org/ squeeze/updates main contrib non-free
deb http://ftp.debian.org/debian/ squeeze main contrib non-free
deb-src http://ftp.debian.org/debian/ squeeze main contrib non-free
deb http://ftp.debian.org/debian/ squeeze-updates main contrib non-free
deb-src http://ftp.debian.org/debian/ squeeze-updates main contrib non-free

# deb cdrom:[Debian GNU/Linux 6.0.3 _Squeeze_ - Official Multi-architecture amd64/i386 NETINST #1 20111008-20:04]/ squeeze main

#deb cdrom:[Debian GNU/Linux 6.0.3 _Squeeze_ - Official Multi-architecture amd64/i386 NETINST #1 20111008-20:04]/ squeeze main

deb http://ftp.uk.debian.org/debian/ squeeze main
deb-src http://ftp.uk.debian.org/debian/ squeeze main

deb http://security.debian.org/ squeeze/updates main
deb-src http://security.debian.org/ squeeze/updates main

# squeeze-updates, previously known as 'volatile'
deb http://ftp.uk.debian.org/debian/ squeeze-updates main
deb-src http://ftp.uk.debian.org/debian/ squeeze-updates main


```

Example above – now save the file

To update the repos we need to issue the following command:

apt-get update

Once that has completed you will be here:



```

Ign http://security.debian.org/ squeeze/updates/non-free Translation-en
Ign http://security.debian.org/ squeeze/updates/non-free Translation-en_GB
Hit http://security.debian.org squeeze/updates Release
Hit http://ftp.debian.org squeeze/main Sources
Hit http://ftp.debian.org squeeze/contrib Sources
Hit http://ftp.debian.org squeeze/non-free Sources
Hit http://ftp.debian.org squeeze/main amd64 Packages
Hit http://ftp.debian.org squeeze/contrib amd64 Packages
Hit http://ftp.debian.org squeeze/non-free amd64 Packages
Hit http://ftp.debian.org squeeze-updates/main Sources/DiffIndex
Hit http://ftp.debian.org squeeze-updates/contrib Sources
Hit http://ftp.debian.org squeeze-updates/non-free Sources
Hit http://security.debian.org squeeze/updates/main Sources
Hit http://ftp.debian.org squeeze-updates/main amd64 Packages/DiffIndex
Hit http://ftp.debian.org squeeze-updates/contrib amd64 Packages
Hit http://ftp.debian.org squeeze-updates/non-free amd64 Packages
Hit http://security.debian.org squeeze/updates/contrib Sources
Hit http://security.debian.org squeeze/updates/non-free Sources
Hit http://security.debian.org squeeze/updates/main amd64 Packages
Hit http://security.debian.org squeeze/updates/contrib amd64 Packages
Hit http://security.debian.org squeeze/updates/non-free amd64 Packages
Hit http://ftp.debian.org squeeze-updates/main amd64 Packages
Reading package lists... Done
root@openmeetings:~#

```

Let's install the needed software by issuing the following commands: **(Please accept the sun-java6-jre license agreement during install)**

apt-get install sun-java6-jdk

apt-get install openoffice.org-writer openoffice.org-calc openoffice.org-impress openoffice.org-draw openoffice.org-math

apt-get install imagemagick

apt-get install gs-gpl

apt-get install libgif-dev xpdf libfreetype6 libfreetype6-dev libjpeg62 libjpeg8 libjpeg8-dev

apt-get install g++


```
apt-get install libjpeg-dev
```

```
apt-get install libdirectfb-dev
```

```
apt-get install libart-2.0-2 libt1-5 zip unzip bzip2 subversion git-core checkinstall yasm texi2html
```


```
libfaac-dev libfaad-dev libmp3lame-dev libsdl1.2-dev libx11-dev libxfixes-dev libxvidcore-dev
```

```
zlib1g-dev libogg-dev sox libvorbis0a libvorbis-dev libgsm1 libgsm1-dev libfaad2 flvtool2 lame
```

Step 4: - Create mysql DB for OM

Now we need to install MYSQL, issue this command (In this case username and password are openmeetings : ompassword)

```
apt-get install mysql-server
```




Enter the password as before “ompassword” and choose ok.

Now let's create the needed DB's for OM 2.x

Issue these commands:

```
mysql -u root -p
```




```
10.17.23.3 - PuTTY
root@openmeetings:~# mysql -u root -p
Enter password: █
```

Enter password “**ompassword**”

Now issue these: (Assuming username **openmeeting** and password = **password**)

```
CREATE DATABASE openmeetings DEFAULT CHARACTER SET 'utf8';  
GRANT ALL PRIVILEGES ON openmeetings.* TO 'openmeetings'@'localhost' IDENTIFIED BY  
'password' WITH GRANT OPTION;  
quit
```



```
10.17.23.3 - PuTTY
root@openmeetings:~# mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 44
Server version: 5.1.61-0+squeezel (Debian)

Copyright (c) 2000, 2011, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE openmeetings DEFAULT CHARACTER SET 'utf8';
Query OK, 1 row affected (0.00 sec)

mysql> GRANT ALL PRIVILEGES ON openmeetings.* TO 'openmeetings'@'localhost' IDENTIFIED BY 'password' WITH GRANT OPTION;
Query OK, 0 rows affected (0.00 sec)

mysql> quit
Bye
root@openmeetings:~# █
```

Successful DB creation shown above.

Step 5: Compile Install SWFTools

Now let's create a temporary working area by issuing these commands:

```
mkdir /usr/adm  
cd /usr/adm
```

Download, compile and install swftools by issuing these commands:


```
wget http://www.swftools.org/swftools-2011-12-15-1229.tar.gz  
tar -zxvf swftools-2011-12-15-1229.tar.gz  
cd swftools-2011-12-15-1229  
./configure --prefix=/usr/local  
make  
make install
```

You can now test it by issuing the following:

```
pdf2swf -V
```

Which should give you the following output:

```
pdf2swf - part of swftools 2011-12-15-1229
```

A screenshot of a PuTTY terminal window titled "10.17.23.3 - PuTTY". The terminal shows the following text: root@openmeetings:/usr/adm/swftools-2011-12-15-1229# pdf2swf -V, pdf2swf - part of swftools 2011-12-15-1229, and root@openmeetings:/usr/adm/swftools-2011-12-15-1229# followed by a green cursor. The terminal background is black, and the text is white. The window has standard Linux window controls (minimize, maximize, close) in the top right corner.

Successful swftools build.

Step 6: Compile and Install ffmpeg

Let's go back to our temporary working area

```
cd /usr/adm
```

Download, compile and install ffmpeg by issuing these commands:

```
wget http://ffmpeg.org/releases/ffmpeg-0.9.1.tar.gz
tar xzf ffmpeg-0.9.1.tar.gz
cd ffmpeg-0.9.1
./configure --enable-libmp3lame --enable-libxvid --enable-libvorbis --enable-libgsm --enable-
libfaac --enable-gpl --enable-nonfree
make
checkinstall
```

N.B - You will be asked a series of question towards the end of the install, press return for each to continue.

Once that has completed you can now test it by issuing the following:

```
ffmpeg --version
```

Which should give you the following output:

```
ffmpeg 0.9.1
```

Step 7: Install JOD Converter

Let's go back to our temporary working area

```
cd /usr/adm
```

Download, extract JOD by issuing these commands: **(We will move the JOD location after the installation of OM 2.x)**

```
wget http://jodconverter.googlecode.com/files/jodconverter-core-3.0-beta-4-dist.zip
unzip jodconverter-core-3.0-beta-4-dist.zip
```

Step 8: Install ANT 1.8.3 for compiling latest OM 2.x

Let's go back to our temporary working area

```
cd /usr/adm
```

Download, extract ANT by issuing these commands:

```
wget http://mirror.catn.com/pub/apache//ant/binaries/apache-ant-1.8.3-bin.tar.gz
tar -zxvf apache-ant-1.8.3-bin.tar.gz
```

Once that has completed you can test it by issuing the following commands:

```
cd /usr/adm/apache-ant-1.8.3/bin
./ant -version
```

This should output the following:

```
Apache Ant(TM) version 1.8.3 compiled on February 26 2012
```

Step 9: Download and compile latest OM 2.x

Again back to our working area:

```
cd /usr/adm
```

Then check out the latest source code using the following:

```
svn checkout https://svn.apache.org/repos/asf/incubator/openmeetings/trunk/singlewebapp/
```

Once that has completed we can then build the source by issuing the following:

```
cd /usr/adm/singlewebapp
/usr/adm/apache-ant-1.8.3/bin/ant -Ddb=mysql
```

This will take a little while depending on your system, once it has finished you should be left the following message:

```
BUILD SUCCESSFUL
```

Step 9a: Install pre-built OM 2.x

Download the latest build from the following link:

<https://builds.apache.org/job/openmeetings/>

The file will be something like the following "apache-openmeetings-incubating-2.xxxxx.tar.gz:
(Where xxx is the date and build version)

So using wget we first go back to our build area like so:

```
cd /usr/adm
mkdir -p singlewebapp/dist
cd singlewebapp/dist
```

Then grab the file and extract it:

```
wget
https://builds.apache.org/job/openmeetings/lastSuccessfulBuild/artifact/singlewebapp/dist/apache-openmeetings-incubating-2.xxxxx.tar.gz
tar -zxvf apache-openmeetings-incubating-2.xxxxx.tar.gz
```

Now download the mysql connector from here:

<http://www.mysql.com/downloads/connector/j/>

```
cd /usr/adm/singlewebapp/dist/red5/webapps/openmeetings/WEB_INF/lib
wget http://www.mysql.com/get/Downloads/Connector-J/mysql-connector-java-5.1.20.zip/from/http://mirrors.ukfast.co.uk/sites/ftp.mysql.com/
unzip mysql-connector-java-5.1.20.zip
cd mysql-connector-java-5.1.20
mv mysql-connector-java-5.1.20-bin.jar
/usr/adm/singlewebapp/dist/red5/webapps/openmeetings/WEB_INF/lib
```

Step 10: Install compiled\Pre-Built OM 2.x

Now we need to move the compiled source into the correct location, in this system we are using /usr/lib/red5, so issue the following commands to move the root folder over:

```
cd /usr/adm/singlewebapp/dist
mv red5/ /usr/lib/
cd /usr/lib/red5
```

Let's move the JOD into place now

```
cp -R /usr/adm/jodconverter-core-3.0-beta-4 /usr/lib/red5/webapps/openmeetings
```

And set some permissions and ownerships

```
chown -R nobody /usr/lib/red5
chmod +x /usr/lib/red5/red5.sh
chmod +x /usr/lib/red5/red5-debug.sh
```

Set the start-up script for OM 2.x by issuing the following:

```
vi /etc/init.d/red5
```

and adding the following:

```
#!/bin/bash
# For RedHat and cousins:
# chkconfig: 2345 85 85
# description: Red5 flash streaming server
# processname: red5
# Created By: Sohail Riaz (sohaileo@gmail.com)
# Modified by Alvaro Bustos
PROG=red5
RED5_HOME=/usr/lib/red5
DAEMON=$RED5_HOME/$PROG.sh
PIDFILE=/var/run/$PROG.pid
# Source function library
# . /etc/rc.d/init.d/functions
[ -r /etc/sysconfig/red5 ] && . /etc/sysconfig/red5
RETVAL=0
case "$1" in
start)
# echo -n "$Starting $PROG: "
    /usr/lib/openoffice/program/soffice "-
accept=socket,host=127.0.0.1,port=8100,tcpNoDelay=1;urp;" -headless -nodefault
-nofirststartwizard -nolockcheck -nologo -norestore & sleep 5
cd $RED5_HOME
    start-stop-daemon --start -c nobody --pidfile $PIDFILE
$DAEMON >/dev/null 2>/dev/null &
RETVAL=$?
if [ $RETVAL -eq 0 ]; then
echo $! > $PIDFILE
# touch /var/lock/subsys/$PROG
fi
# [ $RETVAL -eq 0 ] && success "$$PROG startup" || failure "$$PROG startup"
echo
;;
```

```

stop)
    pkill soffice.bin
    start-stop-daemon --stop --quiet --pidfile $PIDFILE \
        --name java
    rm -f $PIDFILE
echo
[ $RETVAL -eq 0 ] && rm -f /var/lock/subsys/$PROG
;;
restart)
$0 stop
$0 start
;;
status)
status $PROG -p $PIDFILE
RETVAL=$?
;;
*)
echo $"Usage: $0 {start|stop|restart|status}"
RETVAL=1
esac
exit $RETVAL

```

Save the file and then set the permissions like below:

```

chmod +x /etc/init.d/red5
update-rc.d red5 defaults

```

Now we need to move the persistence files so we can connect to mysql, so issue the following:

Make backup copy

```

mv /usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml
/usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml-ori

```

Rename mysql template to persistence.xml

```

mv /usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/mysql_persistence.xml
/usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml

```

Edit the persistence file and add out mysql details, in this case we used “**openmeetings**” and “**password**” – so issue the following:

```

vi /usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml

```

Then change the following

```

, Username=openmeetings

```



```
, Password=password"/>
```

At this stage we are ready to start up OM 2.x for the first time.


```
/etc/init.d/mysql start
```

```
/etc/init.d/red5 start
```

Now open the browser and go to the following link. **N.B remember to change the IP address to your OM2.x server, the one below 10.17.23.3 is just for this example.**

<http://10.17.23.3:5080/openmeetings/install>

If all went well you should now see this page:



Choose the "Continue with STEP 1" link

OpenMeetings - Installation

Userdata	
Username	<input type="text"/>
Userpass	<input type="text"/>
E-Mail	<input type="text"/>
User Time Zone	New Zealand (Etc/GMT+12 (New Zealand))
Organisation(Domains)	
Name	<input type="text"/>
Configuration	
Allow self-registering (allow_frontend_register)	Yes
Send Email to new registered Users (sendEmailAtRegister)	Yes
New Users need to verify their EMail (sendEmailWithVerificationCode)	Yes
Default Rooms of all types will be created	Yes
Mail-Referer (system_email_addr)	noreply@localhost
SMTP-Server (smtp_server)	localhost
SMTP-Server Port(default SmtP-Server Port is 25) (smtp_port)	25
SMTP-Username (email_userpass)	<input type="text"/>
SMTP-Userpass (email_userpass)	<input type="text"/>
Enable TLS in Mail Server Auth	No
Set inviter's email address as ReplyTo in email invitations (inviter.email.as.replyto)	Yes
Default Language	english

The only section we need to fill out at this stage is the following:

Username: **omadmin**

Userpass: **ompassword**

Email: **something@something.com**

TimeZone: **United Kingdom**

Domain Name: **somedomain**

Now click on INSTALL at the bottom of the page, this will then create all the needed tables etc.. - it can take a little while but be patient.

OpenMeetings - Installation Complete!**[Enter the Application](#)**

If your Red5-Server runs on a different Port or on a different domain
[alter the config values of the client](#)

Mailing list


<http://incubator.apache.org/openmeetings/mail-lists.html>

There are some companies that also offer commercial support for Apache OpenMeetings:

<http://incubator.apache.org/openmeetings/commercial-support.html>

Once that has completed you can now enter the application by clicking on the “**Enter the Application**” link

You should see the following logon screen:



Login

Username or mail

Password

Domain: local DB [internal]

Remember login

Not a member? Sign in

[Forgotten your password?](#) [visit Apache OpenMeetings \[Incubating\]](#)


Enter these details to sign in.

Username: **omadmin**

Userpass: **ompassword**

Step 11: Add relevant paths to the configuration

Once logged in go to **Administration > Configuration**



Apache OpenMeetings [Incubating]

Home Recordings Rooms Administration

Hello **firstname lastn**
[town](#) [Timezone](#) [Etc/GM](#)
Unread messages [0](#)
[...Edit your profile](#)

Upload new image

Help and support
[Project website \(http://incubator.apache.org/op](#)
[User mailing list \(http://incubator.apache.org/op](#)

My rooms

My conference room (for 1-16 users)

My webinar room (for 1-120 users)

Users
Manage users and rights

Connections
Manage connections and kick users

Usergroups
Manage usergroups

Conference rooms
Manage conference rooms

Configuration
Manage system settings

Language editor
Manage labels and wording

LDAP
Manage LDAP and ADS configurations

Backup
Export/Import System Backups

Enter

Enter

OpenMeetings 2.X Installation on Debian 64bit Squeeze

Stephen Cottham

15/05/2012

You will see on the left hand pane a list of keys and values, the ones we are interested in are

SWFTools Path [/usr/local/bin](#)
ImageMagick Path [/usr/bin](#)
FFMPEG Path [/usr/local/bin](#)
SoX Path [/usr/bin](#)
JOD Path [/usr/lib/red5/webapps/openmeetings/jodconverter-core-3.0-beta-4/lib](#)

Click on the left hand pane option and then enter the value as above, click on the save button to apply the changes, once you have done each key you should see the following:

The screenshot shows the Apache OpenMeetings Administration interface. The title is "Apache OpenMeetings [Incubating]". The navigation menu includes "Home", "Recordings", "Rooms", and "Administration". The main content area displays a table of configuration keys and values. The table has columns for "ID", "Key", and "Value". The values are as follows:

ID	Key	Value
1	crypt_ClassName	org.openmeetings.utils.crypt.MD5Imple
2	screen_viewer	4
3	allow_frontend_register	1
4	default_group_id	1
5	default_domain_id	1
6	smtp_server	localhost
7	smtp_port	25
8	system_email_addr	noreply@localhost
9	email_username	
10	email_userpass	
11	mail.smtp.starttls.enabl	0
12	application.name	OpenMeetings
13	default_lang_id	1
14	swftools_zoom	72
15	swftools_jpegquality	85
16	swftools_path	/usr/local/bin
17	imagemagick_path	/usr/bin
18	sox_path	/usr/bin
19	ffmpeg_path	
20	office.path	
21	jod.path	/usr/lib/red5/webapps/openmeetings/j
22	rss_feed1	null
23	rss_feed2	null
24	sendEmailAtRegister	1
25	sendEmailWithVerificatic	1
26	default_export_font	TimesNewRoman
27	default.rpc.userid	1
28	red5sip.enable	no
29	red5sip.room_prefix	400
30	red5sip.exten_context	rooms
31	sip.enable	no
32	sip.realm	
33	sip.port	
34	sip.proxyname	
35	sip.tunnel	
36	sip.codebase	
37	sip.forcetunnel	true
38	sip.openxg.enable	no
39	openxg.wrapper.url	
40	openxg.client.id	
41	openxg.client.secret	
42	openxg.client.domain	

On the right side of the interface, there is a "Configuration" panel with fields for "Key", "Value", "Last update", "Updated by", and "Comment".

JOD will find open office in this case so we do not need to set the path.

Step 12: Securing OpenMeetings using encryption (Optional)**12.1 - Generating CSR:**

We can do this in a few ways, the first way I will show here is simply by generating a CSR and inserting these into OpenMeetings.

Create a new keystore and key, use the same password for both: (Taken from OM Website <http://incubator.apache.org/openmeetings/RTMPSAndHTTPS.html>)

```
keytool -keysize 2048 -genkey -alias red5 -keyalg RSA -keystore red5/conf/keystore
```

Enter keystore password:

Re-enter new password:

What is your first and last name?

[Unknown]: <your hostname, e.g demo.openmeetings.de>

What is the name of your organizational unit?

[Unknown]: Dev

What is the name of your organization?

[Unknown]: OpenMeetings

What is the name of your City or Locality?

[Unknown]: Henderson

What is the name of your State or Province?

[Unknown]: Nevada

What is the two-letter country code for this unit?

[Unknown]: US

Is CN=demo.openmeetings.de, OU=Dev, O=OpenMeetings, L=Henderson, ST=Nevada, C=US correct?

[no]: yes

Enter key password for <red5>

Generate a CSR:

```
keytool -certreq -keyalg RSA -alias red5 -file red5.csr -keystore red5/conf/keystore
```

Submit CSR to your CA of choice and receive a signed certificate

Import your chosen CA's root certificate into the keystore (may need to download it from their site - make sure to get the root CA and not the intermediate one)

```
keytool -import -alias root -keystore red5/conf/keystore -trustcacerts -file root.crt
```

(note: you may receive a warning that the certificate already exists in the system wide keystore - import anyway)

Import the intermediate certificate(s) you normally receive with the certificate:

```
keytool -import -alias intermed -keystore red5/conf/ keystore -trustcacerts -file intermediate.crt
```

Import the certificate you received:

```
keytool -import -alias red5 -keystore red5/conf/keystore -trustcacerts -file  
demo.openmeetings.de.crt
```

12.2 – Using Existing certs such as wild card certificates instead of generating a new CSR.

First let's go back to our work area:

```
cd /usr/adm/  
mkdir certs  
cd certs/
```

Using WinSCP or equivalent copy your wild card key and cert files: yourdomain.key.pem and yourdomain.cert.pem - **(These should be in PEM format)**

Now issue the following to convert the files to DER format

```
openssl pkcs8 -topk8 -nocrypt -in apache.key.pem -inform PEM -out key.der -outform DER  
openssl x509 -in apache.cert.pem -inform PEM -out cert.der -outform DER
```

Now we need a couple of files to help us import the DER files into the keystore, so issue the following:

```
wget http://www.agentbob.info/agentbob/80/version/default/part/AttachmentData/data/ImportKey.java  
wget http://www.agentbob.info/agentbob/81/version/default/part/AttachmentData/data/ImportKey.class
```

Then use these commands to import:

```
java ImportKey key.der cert.der
```

Finally move the keystore to the correct location

```
mv /root/keystore.ImportKey /usr/lib/red5/conf/keystore
```

N.B = Alias:importkey Password:importkey (When using the java import key files, you can change the password afterwards)

Now that we have either a new Cert of the wild card cert inside our Keystore we need to make some changes to OM 2.x to use these certificates and thus encrypt communications using HTTPS and RTMPS.

To use RTMPS do the following:

First make some changes to the red5-core.xml file by issuing the following:

```
cd /usr/lib/red5/conf
vi red5-core.xml
```

now uncomment `<!-- RTMPS -->` section by removing the `<!--` and the `-->` leaving this:

```
<bean id="rtmpsMinaloHandler"
  class="org.red5.server.net.rtmps.RTMPSMinaloHandler">
  <property name="handler" ref="rtmpHandler" />
  <property name="codecFactory" ref="rtmpCodecFactory" />
  <property name="rtmpConnManager" ref="rtmpMinaConnManager" />
  <property name="keyStorePassword" value="{rtmps.keystorepass}" />
  <property name="keystoreFile" value="conf/keystore" />
</bean>

<bean id="rtmpsTransport" class="org.red5.server.net.rtmp.RTMPMinaTransport" init-
method="start" destroy-method="stop">
  <property name="ioHandler" ref="rtmpsMinaloHandler" />
  <property name="connectors">
    <list>
      <bean class="java.net.InetSocketAddress">
        <constructor-arg index="0" type="java.lang.String" value="{rtmps.host}" />
        <constructor-arg index="1" type="int" value="{rtmps.port}" />
      </bean>
    </list>
  </property>
  <property name="ioThreads" value="{rtmp.io_threads}" />
  <property name="jmxPollInterval" value="1000" />
  <property name="tcpNoDelay" value="{rtmp.tcp_nodelay}" />
</bean>
```

Save this file and then do the following:

```
cd /usr/lib/red5/conf
vi red5.properties
```

```
set rtmps.port=5443
```

```
rtmps.keystorepass=password (password = password you set on your new keystore)
```

Now edit config.xml by doing the following:

```
cd /usr/lib/red5/webapps/openmeetings/  
vi config.xml
```

Set these following values:

```
<rtmpsslport>5443</rtmpsslport>  
<useSSL>yes</useSSL>  
<proxyType>best</proxyType>
```

To use HTTPS do the following:

First make a backup of the original jee-container file by doing the following:

```
cd /usr/lib/red5/conf  
mv jee-container.xml jee-container.xml.orig
```

Then rename the SSL jee template

```
mv jee-container-ssl.xml jee-container.xml
```

Now edit the config.xml

```
cd /usr/lib/red5/webapps/openmeetings/  
vi config.xml
```

set

```
<protocol>https</protocol>  
<red5httpport>443</red5httpport>
```

Lastly edit red5.properties by doing the following:

```
cd /usr/lib/red5/conf  
vi red5.properties
```

set

```
https.port=443  
http.port=443
```


Now restart OM using the following:

```
/etc/init.d/red5 restart
```

We can now connect using the following link:

<https://yourdomain/openmeetings>

Step 13: Installing Reverse Proxy using Apache Web Server (Optional)

Another way to secure the OpenMeetings service is to use Apache as a reverse proxy, to do this we need to do the following:

First install Apache2 and enabling relevant modules by running the following commands:

```
apt-get install apache2
a2enmod proxy
a2enmod proxy_http
a2enmod ssl
a2enmod headers
a2enmod rewrite
a2enmod cache
/etc/init.d/apache2 restart
```

We can now redirect port 80 (less secure) or port 443 (secure) to port 5080, to do this we need to create a virtual host, to do this do the following:

```
cd /etc/apache2/sites-enabled/
```

Now for SSL redirect (**using a Cert on Apache instead of keystore**) do the following

```
vi om.yourdomain.com-ssl
```

and add the following

```
<IfModule mod_ssl.c>
#NameVirtualHost *:443
ProxyRequests Off
<VirtualHost *:80>
  ServerAdmin hostmaster@domain.com
  ServerName om.yourdomain.com

  ProxyPreserveHost On
  RewriteEngine on
  # Redirect http traffic to https
```

```
RewriteRule ^/(.*)$ https://om.yourdomain.com/$1 [L,R]
</VirtualHost>

<VirtualHost *:443>
  ServerAdmin hostmaster@domain.com
  ServerName om.yourdomain.com

  SSLEngine on
  SSLProxyEngine On
  RequestHeader set Front-End-Https "On"
  ProxyPreserveHost On
  RewriteEngine on
  CacheDisable *

  # Reverse proxy all requests
  RewriteRule ^/(.*) http://om.yourdomain.com:5080/$1 [P]

  SSLCertificateFile /etc/ssl/certs/yourdomain.pem
  SSLCertificateKeyFile /etc/ssl/private/yourdomain.key

  SetEnvIf User-Agent ".*MSIE.*" \
    nokeepalive ssl-unclean-shutdown \
    downgrade-1.0 force-response-1.0
</VirtualHost>
```

You will need SSL certs for this to work, so copy your Key and Cert to the following **locations (use WinSCP or equiv)**

```
/etc/ssl/certs/ = yourdomain.pem
/etc/ssl/private/ = yourdomain.key
```

Now restart apache2

```
/etc/init.d/apache2 restart
```

You can now go to <https://om.yourdomain.com/openmeetings> which will encrypt ONLY the HTTPS components and re-write the address so it doesn't show the 5080 port; it still uses RTMP for flash.

And finally for HTTP redirect and re-write do the following: **(assuming no SSL don't use this in conjunction with the other config – both can be incorporated but this is just for example)**

vi om.yourdomain.com-http

Add the following:

ProxyRequests Off

<VirtualHost *:80>

ServerAdmin hostmaster@domain.com

ServerName om.yourdomain.com

ProxyPreserveHost On

RewriteEngine on

CacheDisable *

Reverse proxy all requests

RewriteRule ^/(.*) http://om.yourdomain.com:5080/\$1 [P]

</VirtualHost>

Then restart Apache with

/etc/init.d/apache2 restart

Now you can access OM with

<http://om.yourdomain.com/>