

**Parts of the guide have been updated from the previous installation documentation from Alvaro Bustos – greenes. -Thanks**

**This guide has been written step by step with screenshots to aid in the successful build of OM.**

**SSL and Reverse proxy steps have been added but are optional.**


**N.B – When copying and pasting commands please check that symbols and character returns are correctly copied across.**

## Installing Debian (Minimal Headless System)


## Step 1: - Base System




Choose 64 Bit install




Choose English




Choose "United Kingdom"




Choose "British English"




Set the hostname, in this case its "openmeetings"




Set your domain, in this case we have used "yourdomain.internal"




Set the root password.




Create new user for server (Non-priv)




Set password for new user




Use guided – entire disk




Select Disk to partition



Choose "All files in one partition"




Choose "Finish partitioning and write changes to disk"




And finally choose "yes"







Choose Debian archive – in this case we are using “United Kingdom”




Any archive will do closest to you; in this case we are using ftp.uk.debian.org




If you use a proxy server then add the details here, if you have full outbound access then just choose continue.




“apt” will now update the local repository information.




Choose not to participate in the survey.



Choose only SSH Server and Standard System utilities.



Choose Yes to install Grub.



Base install has now completed, choose continue to reboot into your new system.

**Step 2: - Setup SSH Environment**

```
Setting kernel variables ...done.
Configuring network interfaces...done.
Starting portmap daemon...
Starting NFS common utilities: statd.
Cleaning up temporary files...
Setting console screen modes.
Skipping font and keymap setup (handled by console-setup).
Setting up console font and keymap...done.
INIT: Entering runlevel: 2
Using makefile-style concurrent boot in runlevel 2.
Starting NFS common utilities: statd.
Starting portmap daemon...Already running..
Starting enhanced syslogd: rsyslogd.
Starting VirtualBox AdditionsVBoxService: 3.2.10_OSE r66523 started. Verbose level = 0
.
Starting ACPI services...
Starting deferred execution scheduler: atd.
Starting periodic command scheduler: cron.
Starting OpenBSD Secure Shell server: sshd.
Starting MTA: exim4.

Debian GNU/Linux 6.0 openmeetings tty1
openmeetings login: _
```

You should now be at the following screen, the next steps are easier done from a remote desktop using an SSH client such as putty. – But first we need to know our IP address, in most cases this was issued by your DHCP server (unless you specified manual network setup during install)

To find your IP address, first logon to your physical machine using root, then issue the following command:

**ifconfig**

This will show the following screen:

```
root@openmeetings:~# ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:22:1d:a1
          inet addr:10.17.23.3  Bcast:10.17.23.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:fe22:1da1/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:433 errors:0 dropped:0 overruns:0 frame:0
          TX packets:30 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:41590 (40.6 KiB)  TX bytes:2756 (2.6 KiB)


lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:8 errors:0 dropped:0 overruns:0 frame:0
          TX packets:8 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:560 (560.0 B)  TX bytes:560 (560.0 B)

root@openmeetings:~# _
```


You can see the IP Address in this case is 10.17.23.3 (Interface eth0)

You can now log off of the server.


From your desktop machine open your SSH client, in this case we will be using the putty client to connect to our new Server.



Enter the details and choose open



The first log on you will receive this message; you can choose yes here and accept the key.




Now log in with your root credentials.

**Step 3: Install Dependent software**

Firstly we need to add some repos to apt to get the required Java version, so first issue this command:

**vi /etc/apt/sources.list**

This will open the following file in vi: (you can use whatever file editor you are comfortable with)



```

10.17.23.3 - PuTTY
#
# deb cdrom:[Debian GNU/Linux 6.0.3 _Squeeze_ - Official Multi-architecture amd64/i386 NETINST #1 20111008-20:04]/ squeeze main
# deb cdrom:[Debian GNU/Linux 6.0.3 _Squeeze_ - Official Multi-architecture amd64/i386 NETINST #1 20111008-20:04]/ squeeze main
deb http://ftp.uk.debian.org/debian/ squeeze main
deb-src http://ftp.uk.debian.org/debian/ squeeze main
deb http://security.debian.org/ squeeze/updates main
deb-src http://security.debian.org/ squeeze/updates main
# squeeze-updates, previously known as 'volatile'
deb http://ftp.uk.debian.org/debian/ squeeze-updates main
deb-src http://ftp.uk.debian.org/debian/ squeeze-updates main
~
~
~
~
"/etc/apt/sources.list" 15 lines, 647 characters


```

Now at the top of this file add the following entries:

```

deb http://security.debian.org/ squeeze/updates main contrib non-free
deb-src http://security.debian.org/ squeeze/updates main contrib non-free
deb http://ftp.debian.org/debian/ squeeze main contrib non-free
deb-src http://ftp.debian.org/debian/ squeeze main contrib non-free
deb http://ftp.debian.org/debian/ squeeze-updates main contrib non-free
deb-src http://ftp.debian.org/debian/ squeeze-updates main contrib non-free
deb http://ftp2.de.debian.org/debian squeeze main non-free
deb http://www.debian-multimedia.org squeeze main

```



```

10.17.23.3 - PuTTY
#
deb http://security.debian.org/ squeeze/updates main contrib non-free
deb http://ftp.debian.org/debian/ squeeze main contrib non-free
deb-src http://ftp.debian.org/debian/ squeeze main contrib non-free
deb http://ftp.debian.org/debian/ squeeze-updates main contrib non-free
deb-src http://ftp.debian.org/debian/ squeeze-updates main contrib non-free
# deb cdrom:[Debian GNU/Linux 6.0.3 _Squeeze_ - Official Multi-architecture amd64/i386 NETINST #1 20111008-20:04]/ squeeze main
# deb cdrom:[Debian GNU/Linux 6.0.3 _Squeeze_ - Official Multi-architecture amd64/i386 NETINST #1 20111008-20:04]/ squeeze main
deb http://ftp.uk.debian.org/debian/ squeeze main
deb-src http://ftp.uk.debian.org/debian/ squeeze main
deb http://security.debian.org/ squeeze/updates main
deb-src http://security.debian.org/ squeeze/updates main
# squeeze-updates, previously known as 'volatile'
deb http://ftp.uk.debian.org/debian/ squeeze-updates main
deb-src http://ftp.uk.debian.org/debian/ squeeze-updates main
~


```

Example above – now save the file

To update the repos we need to issue the following command:

**apt-get update**

Once that has completed you will be here:



```

10.17.23.3 - PuTTY
Ign http://security.debian.org/ squeeze/updates/non-free Translation-en
Ign http://security.debian.org/ squeeze/updates/non-free Translation-en_GB
Hit http://security.debian.org squeeze/updates Release
Hit http://ftp.debian.org squeeze/main Sources
Hit http://ftp.debian.org squeeze/contrib Sources
Hit http://ftp.debian.org squeeze/non-free Sources
Hit http://ftp.debian.org squeeze/main amd64 Packages
Hit http://ftp.debian.org squeeze/contrib amd64 Packages
Hit http://ftp.debian.org squeeze/non-free amd64 Packages
Hit http://ftp.debian.org squeeze-updates/main Sources/DiffIndex
Hit http://ftp.debian.org squeeze-updates/contrib Sources
Hit http://ftp.debian.org squeeze-updates/non-free Sources
Hit http://security.debian.org squeeze/updates/main Sources
Hit http://ftp.debian.org squeeze-updates/main amd64 Packages/DiffIndex
Hit http://ftp.debian.org squeeze-updates/contrib amd64 Packages
Hit http://ftp.debian.org squeeze-updates/non-free amd64 Packages
Hit http://security.debian.org squeeze/updates/contrib Sources
Hit http://security.debian.org squeeze/updates/non-free Sources
Hit http://security.debian.org squeeze/updates/main amd64 Packages
Hit http://security.debian.org squeeze/updates/contrib amd64 Packages
Hit http://security.debian.org squeeze/updates/non-free amd64 Packages
Hit http://ftp.debian.org squeeze-updates/main amd64 Packages
Reading package lists... Done
root@openmeetings:~#

```

Let's install the needed software by issuing the following commands: (Please accept the **sun-java6-jre** license agreement during install)

**apt-get install sun-java6-jdk**

**apt-get install openoffice.org-writer openoffice.org-calc openoffice.org-impress \**  
**openoffice.org-draw openoffice.org-math imagemagick gs-gpl -y**


**apt-get install libgif-dev xpdf libfreetype6 libfreetype6-dev libjpeg62 libjpeg8 \**  
**libjpeg8-dev g++ libjpeg-dev libdirectfb-dev libart-2.0-2 libt1-5 zip unzip bzip2 \**  
**subversion git-core checkinstall yasm texi2html libfaac-dev libfaad-dev libmp3lame-dev \**  
**libsdl1.2-dev libx11-dev libxfixes-dev libxvidcore-dev zlib1g-dev libogg-dev \**  
**sox libvorbis0a libvorbis-dev libgsm1 libgsm1-dev libfaad2 flvtool2 lame -y**

#### Step 4: - Create mysql DB for OM

Now we need to install MYSQL, issue this command (In this case username and password are openmeetings : ompassword)

**apt-get install mysql-server**






Enter the password as before “ompassword” and choose ok.

Now let’s crate the needed DB’s for OM 2.x

Issue these commands:


**mysql -u root -p**



Enter password “**ompassword**”

Now issue these: (Assuming username **openmeeting** and password = **password**)

**CREATE DATABASE openmeetings DEFAULT CHARACTER SET 'utf8';**  
**GRANT ALL PRIVILEGES ON openmeetings.\* TO 'openmeetings'@'localhost' IDENTIFIED BY 'password' WITH GRANT OPTION;**  
**quit**

A screenshot of a PuTTY terminal window titled "10.17.23.3 - PuTTY". The terminal shows a root user at an "openmeetings" machine. The user runs "mysql -u root -p", enters a password, and is prompted to "Welcome to the MySQL monitor. Commands end with ; or \g. Your MySQL connection id is 44. Server version: 5.1.61-0+squeeze1 (Debian)". The user then runs "CREATE DATABASE openmeetings DEFAULT CHARACTER SET 'utf8';" and "GRANT ALL PRIVILEGES ON openmeetings.\* TO 'openmeetings'@'localhost' IDENTIFIED BY 'password' WITH GRANT OPTION;". The terminal shows "Query OK, 1 row affected (0.00 sec)" and "Query OK, 0 rows affected (0.00 sec)" respectively. Finally, the user runs "mysql> quit" and the terminal displays "Bye" and returns to the root prompt "root@openmeetings:~#".

```
root@openmeetings:~# mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 44
Server version: 5.1.61-0+squeeze1 (Debian)

Copyright (c) 2000, 2011, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE openmeetings DEFAULT CHARACTER SET 'utf8';
Query OK, 1 row affected (0.00 sec)

mysql> GRANT ALL PRIVILEGES ON openmeetings.* TO 'openmeetings'@'localhost' IDENTIFIED BY 'password' WITH GRANT OPTION;
Query OK, 0 rows affected (0.00 sec)

mysql> quit
Bye
root@openmeetings:~#
```

Successful DB creation shown above.

#### Step 5: Compile Install SWFTools (2012-04-08-0857)

Now let's create a temporary working area by issuing these commands:

```
mkdir -p /usr/adm
cd /usr/adm
```

Download, compile and install swftools by issuing these commands:


```
wget http://www.swftools.org/swftools-2012-04-08-0857.tar.gz
tar -zxvf swftools-2012-04-08-0857.tar.gz
cd swftools-2012-04-08-0857
./configure
make
make install
```

Once that has completed you can now test it by issuing the following:

```
pdf2swf --version
```

Which should give you the following output:

```
pdf2swf - part of swftools 2012-04-08-0857
```

A screenshot of a PuTTY terminal window titled "10.17.23.3 - PuTTY". The terminal shows a root prompt at an openmeetings machine in the directory /usr/adm/swftools-2011-12-15-1229. The user has entered the command "pdf2swf -v", which outputs "pdf2swf - part of swftools 2011-12-15-1229". The prompt returns to the root user, and a green cursor is visible on the line "root@openmeetings:/usr/adm/swftools-2011-12-15-1229#".

```
10.17.23.3 - PuTTY
root@openmeetings:/usr/adm/swftools-2011-12-15-1229# pdf2swf -v
pdf2swf - part of swftools 2011-12-15-1229
root@openmeetings:/usr/adm/swftools-2011-12-15-1229#
```

Successful swftools build.

#### Step 6: Compile and Install ffmpeg (0.11.1)

Let's go back to our temporary working area

Let's make our temporary working area

```
cd /usr/adm
```

Download, compile and install ffmpeg by issuing these commands:

```
wget http://ffmpeg.org/releases/ffmpeg-0.11.1.tar.gz
tar -zxvf ffmpeg-0.11.1.tar.gz
cd ffmpeg-0.11.1
./configure --enable-libmp3lame --enable-libxvid --enable-libvorbis --enable-libgsm \
--enablelibfaac --enable-gpl --enable-nonfree
make
checkinstall
```

**N.B - You will be asked a series of question towards the end of the install, press return for each to continue.**

Once that has completed you can now test it by issuing the following:

```
ffmpeg -version
```

Which should give you the following output:

```
ffmpeg 0.11.1
```

#### Step 7: Install JOD Converter

Let's go back to our temporary working area

```
cd /usr/adm
```

Download, extract JOD by issuing these commands: **(We will move the JOD location after the installation of OM 2.x)**

```
wget http://jodconverter.googlecode.com/files/jodconverter-core-3.0-beta-4-dist.zip
unzip jodconverter-core-3.0-beta-4-dist.zip
```

#### Step 8: Install ANT 1.8.4 for compiling latest OM 2.x

Let's go back to our temporary working area

```
cd /usr/adm
```

Download, extract ANT by issuing these commands:

```
wget http://mirror.catn.com/pub/apache//ant/binaries/apache-ant-1.8.4-bin.tar.gz
tar -zxvf apache-ant-1.8.4-bin.tar.gz
```

Once that has completed you can test it by issuing the following commands:

```
cd /usr/adm/apache-ant-1.8.4/bin
./ant -version
```

This should output the following:

```
Apache Ant(TM) version 1.8.4 compiled on May 22 2012
```

**Step 9: Download and compile latest OM 2.x**

Again back to our working area:

```
cd /usr/adm
```

Then check out the latest source code using the following:

```
svn checkout http://svn.apache.org/repos/asf/incubator/openmeetings/branches/2.0/
```

Once that has completed we can then build the source by issuing the following:

```
cd /usr/adm/2.0  
/usr/adm/apache-ant-1.8.4/bin/ant clean.all  
/usr/adm/apache-ant-1.8.4/bin/ant -Ddb=mysql
```

This will take a little while depending on your system, once it has finished you should be left the following message:

```
BUILD SUCCESSFUL
```

**Step 9a: Install pre-built OM 2.x**

Download the latest build from the following link:

<https://builds.apache.org/job/openmeetings>

The file will be something like the following "apache-openmeetings-incubating-2.xxxxx.tar.gz:  
(Where xxx is the date and build version)

So using wget we first go back to our build area like so:

```
cd /usr/adm  
mkdir -p singlewebapp/dist  
cd singlewebapp/dist
```

Then grab the file and extract it:

```
wget https://builds.apache.org/job/openmeetings/lastSuccessfulBuild/  
artifact/singlewebapp/dist/apache-openmeetings-incubating-2.xxxxx.tar.gz  
tar -zxvf apache-openmeetings-incubating-2.xxxxx.tar.gz
```

Now download the mysql connector from here:

<http://www.mysql.com/downloads/connector/j/>

```
cd /usr/adm/singlewebapp/dist/red5/webapps/openmeetings/WEB_INF/lib
wget http://www.mysql.com/get/Downloads/Connector-J/\
mysql-connector-java-5.1.20.zip/from/http://mirrors.ukfast.co.uk/sites/\
ftp.mysql.com/
unzip mysql-connector-java-5.1.20.zip
cd mysql-connector-java-5.1.20
mv mysql-connector-java-5.1.20-bin.jar \
/usr/adm/singlewebapp/dist/red5/webapps/openmeetings/WEB_INF/lib
```

#### Step 10: Install compiled\Pre-Built OM 2.x

Now we need to move the compiled source into the correct location, in this system we are using /usr/lib/red5, so issue the following commands to move the root folder over:

```
cd /usr/adm/2.0/dist
mv red5/ /usr/lib/
```

Let's move the JOD into place now

```
cp -R /usr/adm/jodconverter-core-3.0-beta-4 /usr/lib/red5/webapps/openmeetings
```

And set some permissions and ownerships

```
chown -R nobody /usr/lib/red5
chmod +x /usr/lib/red5/red5.sh
chmod +x /usr/lib/red5/red5-debug.sh
```

Set the start-up script for OM 2.x by issuing the following:

```
vi /etc/init.d/red5
```

and adding the following:

```
#!/bin/sh
### BEGIN INIT INFO
# Provides:      red5
# Required-Start:  $remote_fs $syslog
# Required-Stop:  $remote_fs $syslog
# Default-Start:  2 3 4 5
# Default-Stop:   0 1 6
# Short-Description: Starts red5 server for Openmeetings.
```

```

### END INIT INFO
# For RedHat and cousins:
# chkconfig: 2345 85 85
# description: Red5 flash streaming server
# processname: red5
# Created By: Sohail Riaz (sohaileo@gmail.com)
# Modified by Alvaro Bustos
PROG=red5
RED5_HOME=/usr/lib/red5
DAEMON=$RED5_HOME/$PROG.sh
PIDFILE=/var/run/$PROG.pid
# Source function library
# . /etc/rc.d/init.d/functions
[ -r /etc/sysconfig/red5 ] && . /etc/sysconfig/red5
RETVAL=0
case "$1" in
start)
# echo -n "Starting $PROG: "
    cd $RED5_HOME
    start-stop-daemon --start -c nobody --pidfile $PIDFILE --chdir $RED5_HOME --background --
make-pidfile --exec $DAEMON >/dev/null 2>/dev/null &
    RETVAL=$?
    if [ $RETVAL -eq 0 ]; then
        echo $! > $PIDFILE
        # touch /var/lock/subsys/$PROG
    fi
    # [ $RETVAL -eq 0 ] && success "$PROG startup" || failure "$PROG startup"
    echo
;;
stop)
# no longer required as JOD does runs office when it needs to      pkill soffice.bin
    start-stop-daemon --stop --quiet --pidfile $PIDFILE \
        --name java
    rm -f $PIDFILE
    echo
    [ $RETVAL -eq 0 ] && rm -f /var/lock/subsys/$PROG
;;
restart)
    $0 stop
    $0 start
;;
status)
    # status $PROG -p $PIDFILE

```

```
# no longer required as JOD does runs office when it needs to netstat -anp | grep soffice | grep
8100 && /dev/nul && echo $"OpenOffice server is running" || echo $"OpenOffice server is not
running"
    #ps aux | grep -f $PIDFILE && /dev/nul && echo $"$PROG is running" || echo $"$PROG is
not running"
    start-stop-daemon --status --pidfile $PIDFILE
    RETVAL=$?
    [ $RETVAL -eq 0 ] && echo $"$PROG is running"
    [ $RETVAL -eq 1 ] && echo $"$PROG is not running and the pid file exists"
    [ $RETVAL -eq 3 ] && echo $"$PROG is not running"
    [ $RETVAL -eq 4 ] && echo $"$PROG - unable to determine status"
;;
checkports)
    netstat -anp | grep soffice
    netstat -anp | grep java
;;
*)
    echo $"Usage: $0 {start|stop|restart|status|checkports}"
    RETVAL=1
esac
exit $RETVAL
```

Save the file and then set the permissions like below:

```
chmod +x /etc/init.d/red5
update-rc.d red5 defaults
```

Now we need to move the persistence files so we can connect to mysql, so issue the following:

Make backup copy

```
mv /usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml \
/usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml-ori
```

Rename mysql template to persistence.xml

```
mv /usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/mysql_persistence.xml \
/usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml
```

Edit the persistence file and add out mysql details, in this case we used “**openmeetings**” and “**password**” – so issue the following:

```
vi /usr/lib/red5/webapps/openmeetings/WEB-INF/classes/META-INF/persistence.xml
```



Then change the following

```
, Username=openmeetings  
, Password=password"/>
```


At this stage we are ready to start up OM 2.x for the first time.

```
/etc/init.d/red5 start
```

Now open the browser and go to the following link. **N.B remember to change the IP address to your OM2.x server, the one below 10.17.23.3 is just for this example.**

**http://10.17.23.3:5080/openmeetings/install**

If all went well you should now see this page:



Choose the "Continue with STEP 1" link

**OpenMeetings - Installation**

|   |  |
|---|--|
| <b>Userdata</b>   |  |
| Username  | <input type="text"/>                   |
| Userpass  | <input type="text"/>                   |
| E-Mail  | <input type="text"/>                   |
| User Time Zone  | New Zealand (Etc/GMT+12 (New Zealand)) |
| <b>Organisation(Domains)</b>  |  |
| Name  | <input type="text"/>                   |
| <b>Configuration</b>  |  |
| Allow self-registering (allow_frontend_register)  | Yes                                    |
| Send Email to new registered Users<br>(sendEmailAtRegister)                               | Yes                                    |
| New Users need to verify their EMail<br>(sendEmailWithVerificationCode)                   | Yes                                    |
| Default Rooms of all types will be created  | Yes                                    |
| Mail-Referer (system_email_addr)  | noreply@localhost                      |
| SMTP-Server (smtp_server)   | localhost                              |
| SMTP-Server Port(default SmtP-Server Port is 25)<br>(smtp_port)                           | 25                                     |
| SMTP-Username (email_userpass)  | <input type="text"/>                   |
| SMTP-Userpass (email_userpass)  | <input type="text"/>                   |
| Enable TLS in Mail Server Auth  | No                                     |
| Set inviter's email address as ReplyTo in email invitations<br>(inviter.email.as.replyto) | Yes                                    |
| Default Language  | english                                |

The only section we need to fill out at this stage is the following:

Username: **omadmin**

Userpass: **ompassword**

Email: **something@something.com**

TimeZone: **United Kingdom**

Domain Name: **somedomain**

Now click on INSTALL at the bottom of the page, this will then create all the needed tables etc.. - it can take a little while but be patient.

## OpenMeetings - Installation Complete!

### [Enter the Application](#)

If your Red5-Server runs on a different Port or on a different domain  
[alter the config values of the client](#)

### Mailing list


<http://incubator.apache.org/openmeetings/mail-lists.html>

There are some companies that also offer commercial support for Apache OpenMeetings:

<http://incubator.apache.org/openmeetings/commercial-support.html>

Once that has completed you can now enter the application by clicking on the “**Enter the Application**” link

You should see the following logon screen:



Username or mail

Password

Domain local DB [internal]

Remember login

Not a member? Sign in

[Forgotten your password?](#) [visit Apache OpenMeetings \[Incubating\]](#)

Enter these details to sign in.

Username: **omadmin**

Userpass: **ompassword**

**Step 11: Add relevant paths to the configuration**

Once logged in go to **Administration > Configuration**

The screenshot shows the Apache OpenMeetings Administration interface. The top navigation bar includes Home, Recordings, Rooms, and Administration. The Administration menu is expanded, showing options: Users (Manage users and rights), Connections (Manage connections and kick users), Usergroups (Manage usergroups), Conference rooms (Manage conference rooms), Configuration (Manage system settings), Language editor (Manage labels and wording), LDAP (Manage LDAP and ADS configurations), and Backup (Export/Import System Backups). The Configuration option is highlighted with a mouse cursor. On the left, there is a user profile section with a question mark icon and a 'Hello firstname lastname' greeting, followed by links for 'Project website' and 'User mailing list'. Below that is a 'My rooms' section with two entries: 'My conference room (for 1-16 users)' and 'My webinar room (for 1-120 users)', each with a green plus icon and an 'Enter' button.

You will see on the left hand pane a list of keys and values, the ones we are interested in are

|                  |  |
|------------------|--|
| SWFTools Path    | <b><a href="#">/usr/local/bin</a></b>  |
| ImageMagick Path | <b><a href="#">/usr/bin</a></b>  |
| FFMPEG Path      | <b><a href="#">/usr/local/bin</a></b>  |
| SoX Path         | <b><a href="#">/usr/bin</a></b>  |
| JOD Path         | <b><a href="#">/usr/lib/red5/webapps/openmeetings/jodconverter-core-3.0-beta-4/lib</a></b> |

**Click on the left hand pane option and then enter the value as above, click on the save button to apply the changes, once you have done each key you should see the following:**

**Apache OpenMeetings [Incubating]**

Home | Recordings | Rooms | Administration

0 - 50 of 67

| ID | Key                       | Value                                 |
|----|---------------------------|---------------------------------------|
| 1  | crypt_ClassName           | org.openmeetings.utils.crypt.MD5Imple |
| 2  | screen_viewer             | 4                                     |
| 3  | allow_frontend_register   | 1                                     |
| 4  | default_group_id          | 1                                     |
| 5  | default_domain_id         | 1                                     |
| 6  | smtp_server               | localhost                             |
| 7  | smtp_port                 | 25                                    |
| 8  | system_email_addr         | noreply@localhost                     |
| 9  | email_username            |                                       |
| 10 | email_userpass            |                                       |
| 11 | mail.smtp.starttls.enable | 0                                     |
| 12 | application.name          | OpenMeetings                          |
| 13 | default_lang_id           | 1                                     |
| 14 | swftools_zoom             | 72                                    |
| 15 | swftools_jpegquality      | 85                                    |
| 16 | swftools_path             | /usr/local/bin                        |
| 17 | imagemagick_path          | /usr/bin                              |
| 18 | sox_path                  | /usr/bin                              |
| 19 | ffmpeg_path               |                                       |
| 20 | office.path               |                                       |
| 21 | jod.path                  | /usr/lib/red5/webapps/openmeetings/j  |
| 22 | rss_feed1                 | null                                  |
| 23 | rss_feed2                 | null                                  |
| 24 | sendEmailAtRegister       | 1                                     |
| 25 | sendEmailWithVerificatic  | 1                                     |
| 26 | default_export_font       | TimesNewRoman                         |
| 27 | default.rpc.userid        | 1                                     |
| 28 | red5sip.enable            | no                                    |
| 29 | red5sip.room_prefix       | 400                                   |
| 30 | red5sip.exten_context     | rooms                                 |
| 31 | sip.enable                | no                                    |
| 32 | sip.realm                 |                                       |
| 33 | sip.port                  |                                       |
| 34 | sip.proxyname             |                                       |
| 35 | sip.tunnel                |                                       |
| 36 | sip.codebase              |                                       |
| 37 | sip.forcetunnel           | true                                  |
| 38 | sip.openxg.enable         | no                                    |
| 39 | openxg.wrapper.url        |                                       |
| 40 | openxg.client.id          |                                       |
| 41 | openxg.client.secret      |                                       |
| 42 | openxg.client.domain      |                                       |

**Configuration**

Key

Value

Last update

Updated by

Comment

**JOD will find open office in this case so we do not need to set the path.**

**Step 12: Securing OpenMeetings using encryption (Optional)****12.1 - Generating CSR:**

We can do this in a few ways, the first way I will show here is simply by generating a CSR and inserting these into OpenMeetings.

Create a new keystore and key, use the same password for both: (Taken from OM Website <http://incubator.apache.org/openmeetings/RTMPSAndHTTPS.html>)

```
keytool -keysize 2048 -genkey -alias red5 -keyalg RSA -keystore red5/conf/keystore
```

Enter keystore password:

Re-enter new password:

What is your first and last name?

[Unknown]: <your hostname, e.g demo.openmeetings.de>

What is the name of your organizational unit?

[Unknown]: Dev

What is the name of your organization?

[Unknown]: OpenMeetings

What is the name of your City or Locality?

[Unknown]: Henderson

What is the name of your State or Province?

[Unknown]: Nevada

What is the two-letter country code for this unit?

[Unknown]: US

Is CN=demo.openmeetings.de, OU=Dev, O=OpenMeetings, L=Henderson, ST=Nevada, C=US correct?

[no]: yes

Enter key password for <red5>

Generate a CSR:

```
keytool -certreq -keyalg RSA -alias red5 -file red5.csr -keystore red5/conf/keystore
```

Submit CSR to your CA of choice and receive a signed certificate

Import your chosen CA's root certificate into the keystore (may need to download it from their site - make sure to get the root CA and not the intermediate one)

```
keytool -import -alias root -keystore red5/conf/keystore -trustcacerts -file root.crt
```

(note: you may receive a warning that the certificate already exists in the system wide keystore - import anyway)

Import the intermediate certificate(s) you normally receive with the certificate:

```
keytool -import -alias intermed -keystore red5/conf/ keystore -trustcacerts -file intermediate.crt
```

Import the certificate you received:

```
keytool -import -alias red5 -keystore red5/conf/keystore -trustcacerts -file  
demo.openmeetings.de.crt
```

## 12.2 – Using Existing certs such as wild card certificates instead of generating a new CSR.

First let's go back to our work area:

```
cd /usr/adm/  
mkdir certs  
cd certs/
```

Using WinSCP or equivalent copy your wild card key and cert files: yourdomain.key.pem and yourdomain.cert.pem - **(These should be in PEM format)**

Now issue the following to convert the files to DER format

```
openssl pkcs8 -topk8 -nocrypt -in apache.key.pem -inform PEM -out key.der -outform DER  
openssl x509 -in apache.cert.pem -inform PEM -out cert.der -outform DER
```

Now we need a couple of files to help us import the DER files into the keystore, so issue the following:

```
wget http://www.agentbob.info/agentbob/80/version/default/part/AttachmentData/data/ImportKey.java  
wget http://www.agentbob.info/agentbob/81/version/default/part/AttachmentData/data/ImportKey.class
```

Then use these commands to import:

```
java ImportKey key.der cert.der
```

Finally move the keystore to the correct location

```
mv /root/keystore.ImportKey /usr/lib/red5/conf/keystore
```

**N.B = Alias:importkey Password:importkey (When using the java import key files, you can change the password afterwards)**

Now that we have either a new Cert of the wild card cert inside our Keystore we need to make some changes to OM 2.x to use these certificates and thus encrypt communications using HTTPS and RTMPS.

To use RTMPS do the following:

First make some changes to the red5-core.xml file by issuing the following:

```
cd /usr/lib/red5/conf
vi red5-core.xml
```

now uncomment `<!-- RTMPS -->` section by removing the `<!--` and the `-->` leaving this:

```
<bean id="rtmpsMinaloHandler"
  class="org.red5.server.net.rtmps.RTMPSMinaloHandler">
  <property name="handler" ref="rtmpHandler" />
  <property name="codecFactory" ref="rtmpCodecFactory" />
  <property name="rtmpConnManager" ref="rtmpMinaConnManager" />
  <property name="keyStorePassword" value="{rtmps.keystorepass}" />
  <property name="keystoreFile" value="conf/keystore" />
</bean>

<bean id="rtmpsTransport" class="org.red5.server.net.rtmp.RTMPMinaTransport" init-
method="start" destroy-method="stop">
  <property name="ioHandler" ref="rtmpsMinaloHandler" />
  <property name="connectors">
    <list>
      <bean class="java.net.InetSocketAddress">
        <constructor-arg index="0" type="java.lang.String" value="{rtmps.host}" />
        <constructor-arg index="1" type="int" value="{rtmps.port}" />
      </bean>
    </list>
  </property>
  <property name="ioThreads" value="{rtmp.io_threads}" />
  <property name="jmxPollInterval" value="1000" />
  <property name="tcpNoDelay" value="{rtmp.tcp_nodelay}" />
</bean>
```

Save this file and then do the following:

```
cd /usr/lib/red5/conf
vi red5.properties
```

```
set rtmps.port=5443
```

```
rtmps.keystorepass=password (password = password you set on your new keystore)
```



Now edit config.xml by doing the following:

```
cd /usr/lib/red5/webapps/openmeetings/  
vi config.xml
```

Set these following values:

```
<rtmpsslport>5443</rtmpsslport>  
<useSSL>yes</useSSL>  
<proxyType>best</proxyType>
```

**To use HTTPS do the following:**

First make a backup of the original jee-container file by doing the following:

```
cd /usr/lib/red5/conf  
mv jee-container.xml jee-container.xml.orig
```

Then rename the SSL jee template

```
mv jee-container-ssl.xml jee-container.xml
```

Now edit the config.xml

```
cd /usr/lib/red5/webapps/openmeetings/  
vi config.xml
```

set

```
<protocol>https</protocol>  
<red5httpport>443</red5httpport>
```

Lastly edit red5.properties by doing the following:

```
cd /usr/lib/red5/conf  
vi red5.properties
```

set

```
https.port=443  
http.port=443
```

Now restart OM using the following:

```
/etc/init.d/red5 restart
```

We can now connect using the following link:

```
https://yourdomain/openmeetings
```

### Step 13: Installing Reverse Proxy using Apache Web Server (Optional)

Another way to secure the OpenMeetings service is to use Apache as a reverse proxy, to do this we need to do the following:

First install Apache2 and enabling relevant modules by running the following commands:

```
apt-get install apache2
a2enmod proxy
a2enmod proxy_http
a2enmod ssl
a2enmod headers
a2enmod rewrite
a2enmod cache
/etc/init.d/apache2 restart
```

We can now redirect port 80 (less secure) or port 443 (secure) to port 5080, to do this we need to create a virtual host, to do this do the following:

```
cd /etc/apache2/sites-enabled/
```

Now for SSL redirect (**using a Cert on Apache instead of keystore**) do the following

```
vi om.yourdomain.com-ssl
```

and add the following

```
<IfModule mod_ssl.c>
#NameVirtualHost *:443
ProxyRequests Off
<VirtualHost *:80>
  ServerAdmin hostmaster@domain.com
  ServerName om.yourdomain.com

ProxyPreserveHost On
RewriteEngine on
# Redirect http traffic to https
```

```
RewriteRule ^/(.*)$ https://om.yourdomain.com/$1 [L,R]
</VirtualHost>

<VirtualHost *:443>
  ServerAdmin hostmaster@domain.com
  ServerName om.yourdomain.com

  SSLEngine on
  SSLProxyEngine On
  RequestHeader set Front-End-Https "On"
  ProxyPreserveHost On
  RewriteEngine on
  CacheDisable *

  # Reverse proxy all requests
  RewriteRule ^/(.*) http://om.yourdomain.com:5080/$1 [P]

  SSLCertificateFile /etc/ssl/certs/yourdomain.pem
  SSLCertificateKeyFile /etc/ssl/private/yourdomain.key

  SetEnvIf User-Agent ".*MSIE.*" \
  nokeepalive ssl-unclean-shutdown \
  downgrade-1.0 force-response-1.0
</VirtualHost>
```

You will need SSL certs for this to work, so copy your Key and Cert to the following **locations (use WinSCP or equiv)**

```
/etc/ssl/certs/ = yourdomain.pem
/etc/ssl/private/ = yourdomain.key
```

Now restart apache2

```
/etc/init.d/apache2 restart
```

You can now go to <https://om.yourdomain.com/openmeetings> which will encrypt ONLY the HTTPS components and re-write the address so it doesn't show the 5080 port; it still uses RTMP for flash.

And finally for HTTP redirect and re-write do the following: **(assuming no SSL don't use this in conjunction with the other config – both can be incorporated but this is just for example)**

```
vi om.yourdomain.com-http
```

Add the following:

```
ProxyRequests Off
```

```
<VirtualHost *:80>
```

```
ServerAdmin hostmaster@domain.com
```

```
ServerName om.yourdomain.com
```

```
ProxyPreserveHost On
```

```
RewriteEngine on
```

```
CacheDisable *
```

```
# Reverse proxy all requests
```

```
RewriteRule ^/(.*) http://om.yourdomain.com:5080/$1 [P]
```

```
</VirtualHost>
```

Then restart Apache with

```
/etc/init.d/apache2 restart
```

Now you can access OM with

```
http://om.yourdomain.com/
```