



Installation of Apache OpenMeetings 3.1.1 on openSUSE 13.2

This tutorial is made based on fresh installations of

openSUSE-13.2-KDE-Live-x86_64.iso

It is tested with positive result. We will use the Apache's binary version OpenMeetings 3.1.1 stable, that is to say will suppress his compilation. It is done step by step.

19-5-2016

Starting...

1)

----- Update Operative System -----

Update operative system:

[zypper refresh](#)

[zypper update](#)

2)

----- Installation of OpenJava -----

Java is necessary to work OpenMeetings. Should install OpenJava and the plugin icedtea-web for record conference room and share desktop:

```
zypper install -y java icedtea-web
```

3)

----- **Installation of LibreOffice** -----

OpenMeetings need LibreOffice to convert to pdf the uploaded office files.

Maybe it is installed but for iso server:

```
zypper install -y libreoffice
```

4)

----- **Installation of necessary packages and libraries** -----

Should install packages and libraries we'll need later:

(Only one line with space between both)

```
zypper install -y gcc ghostscript unzip freetype freetype-devel ncurses ncurses-devel make libzlib-devel libtool bzip2 file-roller git autoconf automake pkg-config nmap wget
```

5)

----- **Installation ImageMagick, Sox and Swftools** -----

ImageMagick will work with images files. Should install it and some more libraries:

```
zypper install -y ImageMagick giflib-devel
```

Sox work the sound:

```
zypper install sox
```

Swftools work converting to swf, flash file, the uploaded files. Don't use a newer version, maybe have not pdf2swf.

Add media repo:

(Only one line with space between both)

zypper ar

http://download.opensuse.org/repositories/multimedia:/apps/openSUSE_13.2/multimedia:apps.repo

zypper refresh

...accept repository clave for ever, and we procede to install swftools:

zypper install -y swftools

Block the version, to prevent changes:

zypper al swftools

6)

----- **Installation of Adobe Flash Player** -----

OpenMeetings even need Adobe Flash Player for rooms.

Add Adobe repo:

`rpm -ivh http://linuxdownload.adobe.com/adobe-release/adobe-release-x86_64-1.0-1.noarch.rpm`

`rpm --import /etc/pki/rpm-gpg/RPM-GPG-KEY-adobe-linux`

zypper refresh

...and install flash player:

zypper install -y flash-player

7)

----- **Installation of Jodconverter** -----

Jodconverter work to convert uploaded files.

`cd /opt`

`wget http://jodconverter.googlecode.com/files/jodconverter-core-3.0-beta-4-dist.zip`

`unzip jodconverter-core-3.0-beta-4-dist.zip`

8)

----- **Compilation of Ffmpeg** -----

FFmpeg work video. Will install paquets and libraries.

```
zypper install -y glibc imlib2 imlib2-devel mercurial cmake nano
```

```
zypper install -y freetype2-devel libfreetype6
```

```
zypper install -y libogg-devel libtheora-devel libvorbis-devel libvpx-devel
```

This ffmpeg compilation is based on this url, but updated file versions 19-5-2016:

<https://trac.ffmpeg.org/wiki/CompilationGuide/Centos>

As it is, the compilation in this url gives errors when compiling.

Then i supress one step in the url, add some one and modify others. Now works properly without error. Audio-video recording is synchronized. Mp4 and Ogg are right.

So, i made a script to download, compile and install ffmpeg on openSUSE 13.2. It is tested and is ok.

During the x265 compilation, will look like stop for a minutes, in a text that say: **41%**, but not always. Don't worry, everything is goeing right. Be patience.

Download the script:

```
cd /opt
```

(Only one line without space between both)

```
wget https://cwiki.apache.org/confluence/download/attachments/27838216/ffmpeg-opensuse.sh?version=1&modificationDate=1463725518178&api=v2
```

..push Ctrl+c in keyboard, when the download is finished.

Rename the script:

```
mv ffmpeg-opensuse.sh?version=1 ffmpeg-opensuse.sh
```

...concede execution permission:

```
chmod +x ffmpeg-opensuse.sh
```

...and run it. Will spend about 30 minutes in the compilation...remember, be patience:

```
./ffmpeg-opensuse.sh
```

When is finished, will appear a text: **FFMPEG Compilation and Installation Finished!**

Then, you can go to **step 9)**

But if you prefer copy and paste, i **don't advise**, here is the text script:

[nano /opt/ffmpeg-opensuse.sh](#)

...copy the green text **from here**:

```
# Script ffmpeg compilation for openSUSE 13.2 and ApacheOpenMeetings tutorial
# Alvaro Bustos, thanks to Hunter.
# 19-5-2016
# Install libraries
zypper install -y autoconf automake cmake freetype-devel gcc gcc-c++ git libtool make mercurial
nasm pkgconfig zlib-devel

# Install yasm from repos
zypper install -y yasm

# Create a temporary directory for sources.
SOURCES=$(mkdir ~/ffmpeg_sources)
cd ~/ffmpeg_sources

# Download the necessary sources.
#git clone --depth 1 git://git.videolan.org/x264
wget http://download.videolan.org/pub/x264/snapshots/x264-snapshot-20160518-2245-
stable.tar.bz2
hg clone https://bitbucket.org/multicoreware/x265
git clone --depth 1 git://git.code.sf.net/p/opencore-amr/fdk-aac
curl -L -O http://downloads.sourceforge.net/project/lame/lame/3.99/lame-3.99.5.tar.gz
git clone http://git.opus-codec.org/opus.git
curl -O http://downloads.xiph.org/releases/ogg/libogg-1.3.2.tar.gz
curl -O http://downloads.xiph.org/releases/vorbis/libvorbis-1.3.5.tar.gz
wget http://downloads.xiph.org/releases/theora/libtheora-1.1.1.tar.gz
git clone --depth 1 https://chromium.googlesource.com/webm/libvpx.git
wget http://ffmpeg.org/releases/ffmpeg-3.0.2.tar.gz

# Unpack files
for file in `ls ~/ffmpeg_sources/*.tar.*`; do
tar -xvf $file
done

cd x264-snapshot*
./configure --prefix="$HOME/ffmpeg_build" --bindir="$HOME/bin" --enable-static && make &&
make install && make distclean; cd ..

cd x265/build/linux
cmake -G "Unix Makefiles" -DCMAKE_INSTALL_PREFIX="$HOME/ffmpeg_build"
-DENABLE_SHARED:bool=off ../../source && make && make install; cd ~/ffmpeg_sources

cd fdk-aac
```

```
autoreconf -fiv && ./configure --prefix="$HOME/ffmpeg_build" --disable-shared && make &&
make install && make distclean; cd ..
```

```
cd lame-*/
./configure --prefix="$HOME/ffmpeg_build" --bindir="$HOME/bin" --disable-shared --enable-
nasm && make && make install && make distclean; cd ..
```

```
cd opus
autoreconf -fiv && ./configure --prefix="$HOME/ffmpeg_build" --disable-shared && make &&
make install && make distclean; cd ..
```

```
cd libogg-*/
./configure --prefix="$HOME/ffmpeg_build" --disable-shared && make && make install &&
make distclean; cd ..
```

```
cd libvorbis-*/
LDLFLAGS="-L$HOME/ffmeg_build/lib64" CPPFLAGS="-I$HOME/ffmpeg_build/include"
./configure --prefix="$HOME/ffmpeg_build" --with-ogg="$HOME/ffmpeg_build" --disable-shared
&& make && make install && make distclean; cd ..
```

```
cd libtheora-*/
./configure --prefix="$HOME/ffmpeg_build" --with-ogg="$HOME/ffmpeg_build" --disable-
examples --disable-shared --disable-sdltest --disable-vorbistest && make && make install; cd ..
```

```
cd libvpx
./configure --prefix="$HOME/ffmpeg_build" --disable-examples && make && make install &&
make clean; cd ..
```

```
cp /root/ffmpeg_build/lib/pkgconfig/x264.pc /root/ffmpeg_build/lib64/pkgconfig
```

```
cp /root/ffmpeg_build/lib/pkgconfig/x265.pc /root/ffmpeg_build/lib64/pkgconfig
```

```
cd ffmpeg-*/
PKG_CONFIG_PATH="$HOME/ffmpeg_build/lib64/pkgconfig" ./configure
--prefix="$HOME/ffmpeg_build" --extra-cflags="-I$HOME/ffmpeg_build/include" --extra-
ldflags="-L$HOME/ffmpeg_build/lib64" --bindir="$HOME/bin" --pkg-config-flags="--static"
--enable-gpl --enable-nonfree --enable-libfdk_aac --enable-libfreetype --enable-libmp3lame
--enable-libopus --enable-libvorbis --enable-libvpx --enable-libx264 --enable-libx265 --enable-
libtheora && make && make install && make distclean && hash -r; cd ..
```

```
cd ~/bin
cp ffmpeg ffprobe ffserver lame x264 /usr/local/bin
```

```
cd ~/ffmpeg_build/bin
cp x265 /usr/local/bin
```

```
echo "FFMPEG Compilation and Installation Finished!"
```

...to here.

Concede permission of execution:

```
chmod +x /opt/ffmpeg-opensuse.sh
```

```
cd /opt
```

Now be connected to Internet, run the script and wait some long minutes while the compilation:

```
./ffmpeg-opensuse.sh
```

All the compiled files will be installed on: **/usr/local/bin**

9)

----- **Installation MariaDB database server** -----

MariaDB is the database server.

We install it:

```
zypper install -y mariadb mariadb-tools
```

...and run mariadb:

```
systemctl start mysql.service
```

Give a password to mariadb root . Please, modify **new-password** by your own.

```
mysqladmin -u root password new-password
```

Make a database for OpenMeetings:

```
mysql -u root -p
```

...will ask for the root password you does just now:

```
CREATE DATABASE open311 DEFAULT CHARACTER SET 'utf8';
```

...now do a new user with his own password:

```
CREATE USER 'hola'@'localhost' IDENTIFIED BY '123456';
```

...and give privileges to this user on the open311 database:

```
GRANT ALL PRIVILEGES ON open311.* TO 'hola'@'localhost' WITH GRANT OPTION;
```

```
FLUSH PRIVILEGES;
```

quit

```
open311 ..... name of the database  
hola ..... user for that database  
123456 ..... password of that user
```

To start, restart or stop mariadb:

```
systemctl start mysql.service  
  
systemctl restart mysql.service  
  
systemctl stop mysql.service
```

10)

----- **Installation of OpenMeetings** -----

We'll install OpenMeetings in /opt/red5311. All the following information will be based on this directory.

Make the folder:

```
mkdir /opt/red5311
```

```
cd /opt/red5311
```

...and download the OpenMeetings file:

```
wget http://apache.rediris.es/openmeetings/3.1.1/bin/apache-openmeetings-3.1.1.zip
```

```
unzip apache-openmeetings-3.1.1.zip
```

...save the unloaded file to /opt:

```
mv apache-openmeetings-3.1.1.zip /opt
```

Download and install the connector between OpenMeetings and MariaDB:

```
cd /opt
```

(Only one line without space between both)

```
wget http://repo1.maven.org/maven2/mysql/mysql-connector-java/5.1.38/mysql-connector-java-5.1.38.jar
```

...and copy it to where must be:

`cp /opt/mysql-connector-java-5.1.38.jar /opt/red5311/webapps/openmeetings/WEB-INF/lib`

Now we are going to configure OpenMeetings for our database in MariaDB:

`nano /opt/red5311/webapps/openmeetings/WEB-INF/classes/META-INF/mysql_persistence.xml`

Modify on line 72:

```
, Url=jdbc:mysql://localhost:3306/openmeetings
```

```
...to
```

```
, Url=jdbc:mysql://localhost:3306/open311
```

...it is the name of the database that we did initially.

Modify on line 77:

```
, Username=root
```

```
...to
```

```
, Username=hola
```

...is the user that we did initially for the database.

Modify on line 78:

```
, Password=" />
```

```
...to
```

```
, Password=123456" />
```

...it is the password that we did initially for the user "hola" in the database.

Logically if initially you choose another name and password for the database, you will to change them here.

Push **Ctrl+x**, **Y** and **Enter** in the keyboard, to leave nano.

We protect the access to the file:

(Only one line without space between both)

```
chmod 640 /opt/red5311/webapps/openmeetings/WEB-INF/classes/META-INF/mysql_persistence.xml
```

11)

----- Script to launch red5-OpenMeetings -----

Build a script to start and stop red5-OpenMeetings, that we'll call red5:

```
cd /opt
```

```
nano /etc/init.d/red5
```

...please, copy and past the text **from here**:

```
#
#!/bin/sh -e
#
# Startup script for Red5

export RED5_HOME=/opt/red5311

start_red5="$RED5_HOME/red5.sh start"
stop_red5="$RED5_HOME/red5-shutdown.sh stop"

start() {
    echo -n "Starting Red5: "
    ${start_red5} &
    echo "done."
}
stop() {
    echo -n "Shutting down Red5: "
    ${stop_red5}
    echo "done."
}

case "$1" in
    start)
        start
        ;;
    stop)
        stop
        ;;
    restart)
        stop
        start
        ;;
    *)
        echo "Usage: $0 {start|stop|restart}"
        exit 1
    esac
```

```

    sleep 10
    start
    ;;
*)
    echo "Usage: $0 {start|stop|restart}"
esac

exit 0

```

...to here.

If you made the installation in any other path, can modify the line:

```
RED5_HOME=/opt/red5311
```

...to

```
RED5_HOME=/your-path-installation
```

Push **Ctrl+x**, **Y** and **Enter** in the keyboard, to save and leave nano.

Concede execution permission:

```
chmod +x /etc/init.d/red5
```

12)

----- Run red5-OpenMeetings -----

Restart mariadb:

```
systemctl restart mysql.service
```

...and start red5-OpenMeetings, maybe in other window shell:

```
/etc/init.d/red5 start
```

...wait 40 seconds at least, in order that red5 runing completely, and later can go to:

<http://localhost:5080/openmeetings/install>

...there will appear a page similar to this one:

OpenMeetings

1. Enabling Image Upload and import to whiteboard

- o Install **ImageMagick** on the server, you can get more information on <http://www.imagemagick.org> regarding installation. The instructions for installation can be found there <http://www.imagemagick.org/script/binary-releases.php>, however on most linux systems you can get it via your favorite package managers (apt-get it)

2. Enabling import of PDFs into whiteboard

- o Install **GhostScript** on the server, you can get more information on <http://pages.cs.wisc.edu/~ghost/> regarding installation. The instructions for installation can be found there, however on most linux systems you can get it via your favorite package managers (apt-get it).
- o Install **SWFTools** on the server, you can get more information on <http://www.swftools.org/> regarding installation. Some of the Linux distributions already have it in there package manager see <http://packages.debian.org/unstable/utils/swftools>, the recommended version of **SWFTools** is 0.9 as prior version have a bug that does lead to wrong object dimensions in the Whiteboard

3. Enabling import of .doc, .docx, .ppt, .pptx, ... all Office Documents into whiteboard

- o **OpenOffice-Service** started and listening on port 8100, see [OpenOfficeConverter](#) for details

4. Enabling Recording and import of .avi, .flv, .mov and .mp4 into whiteboard

- o Install **FFmpeg**. You should get FFmpeg in an up to date copy! For Windows you can download a Build for example from <http://ffmpeg.arozcru.org/builds/> Linux or OSX Users should be able to use one of the various Installation Instructions on the Web. You need to enable libmp3lame!
- o Install **SoX** <http://sox.sourceforge.net/>. You should install SoX in a up to date copy! SoX 12.xx will NOT work!

If you have further questions or need support in installation or hosting:

Community-Support:

[Mailing lists](#)

Commercial-Support:

...push on  (bottom), and will show the default database configuration with Derby, but we should use MySQL, (MariaDB):

OpenMeetings

DB configuration

Recommendation for production environment

By default OpenMeetings uses the integrated [Apache Derby](#) database. For production environment you should consider using [MySQL](#), [PostgreSQL](#), [IBM DB2](#), [MSSQL](#) or [Oracle](#)


Choose DB type

Specify the name of the database

Specify DB user

Specify DB password

...then, scroll and **Choose DB type** to MySQL:




The screenshot shows the 'OpenMeetings' application window with the 'DB configuration' section. It includes a recommendation for a production environment and several input fields for database settings. The 'Choose DB type' dropdown is set to 'MySQL'. Other fields include 'Specify DB host' (localhost), 'Specify DB port' (3306), 'Specify the name of the database' (open311), 'Specify DB user' (hola), and 'Specify DB password' (123456). A 'Check' button is located at the bottom right of the configuration area. Navigation buttons '<', '>', '>>', and 'Finish' are at the bottom of the window.

Choose DB type	MySQL
Specify DB host	localhost
Specify DB port	3306
Specify the name of the database	open311
Specify DB user	hola
Specify DB password	123456

...will show the data base configuration we made in step 10, or with your own modifications.

Please, push button and will go to:



The screenshot shows the 'OpenMeetings' application window with the 'Userdata' section. It contains input fields for 'Username', 'Userpass', and 'EMail', and a dropdown menu for 'User Time Zone' set to 'Europe/Madrid'. Below this is the 'Group(Domains)' section with a 'Name' input field. Navigation buttons '<', '>', '>>', and 'Finish' are at the bottom of the window.

Username	<input type="text"/>
Userpass	<input type="text"/>
EMail	<input type="text"/>
User Time Zone	Europe/Madrid

Group(Domains)	
Name	<input type="text"/>

Now we must introduce the followings data, in order can continue:

Username = a-name ...this user will be administrator.

Userpass = a-password ...for the previous user.

Email = email-adress ...of the previous user.

User Time Zone = Country where is this server

Name = example-openmeetings ...group name to choose.

When the installation be finished, shouldd configure the rest.


Now go to bottom, and touch the button  (double arrow). Will show this window:



Clic **Finish** button...wait a seconds untill the tables are fill in the database.

When has concluded, this another page will appear. **Don't** clic on [Enter the Application](#). First is need it to restart the server. Please, open a new terminal and restart red5:


[/etc/init.d/red5 restart](#)



Now yes, you can clic on [Enter the Application](#), or go with your browser to:

<http://localhost:5080/openmeetings>

...and will take us to the entry of OpenMeetings:



Introduce the user's name and the password that you have chosen during the installation, push **Sign in** and...

...Congratulations!

The next time that you like to accede OpenMeetings, would be:

<http://localhost:5080/openmeetings>

Remember to open in the server, the two following ports:

1935 5080

...in order that it could accede to OpenMeetings from other machines in Lan or Internet.

13)

----- **OpenMeetings's configuration** -----

Once you acced to OpenMeetings, go to:

Administration → Configuration



OpenMeetings

Home ▾ Rooms ▾ Recordings ▾ Administration ▾

Welcome

 **Hello firstname lastname**


Timezone Europe/Madrid
Unread messages [0](#)
[Edit your profile](#)

[Upload new image](#)

Help and support

[Project website \(http://openmeetings.apache.org\)](http://openmeetings.apache.org)
[User mailing list \(http://openmeetings.apache.org/mail-lists.html\)](http://openmeetings.apache.org/mail-lists.html)
[Network testing](#)

...introduce the parameters for the conversion of files, the audio and the video:



Home ▾ Rooms ▾ Recordings ▾ Administration ▾

50 Search

ID	Key	Value
4	email_domain_registry	
5	default_group_id	1
6	smtp_server	localhost
7	smtp_port	25
8	system_email_addr	
9	email_username	
10	email_userpass	123456
11	mail.smtp.starttls.enable	0
12	mail.smtp.connection.timeout	30000
13	mail.smtp.timeout	30000
14	application_name	OpenMeetings
15	default_lang_id	1
16	swftools_zoom	100
17	swftools_jpegquality	85
18	swftools_path	
19	imagemagick_path	
20	sox_path	
21	ffmpeg_path	
22	office.path	
23	jod.path	

configuration

Key

Value

Last update 26.02.2016 08:48:28

Updated by

Comment

1 2 3

Clic on: **swftools_path**...and to the right in **Value** type: [/usr/bin](#)

Clic on: **imagemagick_path**...and to the right in **Value** type: [/usr/bin](#)

Clic on: **sox_path**...and to the right in **Value** type: [/usr/bin](#)

Clic on: **ffmpeg_path**...and to the right in **Value** type: [/usr/local/bin](#)

Clic on: **office.path**...and to the right in **Value** type: [/usr/lib64/libreoffice](#)

Clic on: **jod.path**...and to the right in **Value** type: [/opt/jodconverter-core-3.0-beta-4/lib](#)

Remember save after each change (**arrow number 3**, in the up screenshot).

Now there is OpenMeetings ready to work rightly.

We are going to remove files that already do not serve us, if you do not want to save them:

```
rm -f /opt/jodconverter-core-3.0-beta-4-dist.zip
```

```
rm -f /opt/mysql-connector-java-5.1.38.jar
```

And this is all.

If you have some doubt or question, please raise it in the Apache OpenMeetings forums:

<http://openmeetings.apache.org/mail-lists.html>

Thank you.

Alvaro Bustos