

# KIP-789: Use localhost:9092 as default bootstrap-server /broker-list in client tools

- Status
- Motivation
- Public Interfaces
- Proposed Changes
- Compatibility, Deprecation, and Migration Plan
- Rejected Alternatives

This page is meant as a template for writing a [KIP](#). To create a KIP choose Tools->Copy on this page and modify with your content and replace the heading with the next KIP number and a description of your issue. Replace anything in *italics* with your own description.

## Status

**Current state:** [One of "Under Discussion", "Accepted", "Rejected"]

**Discussion thread:** [here](#) [Change the link from the KIP proposal email archive to your own email thread]

**JIRA:** [here](#) [Change the link from KAFKA-1 to your own ticket]

Please keep the discussion on the mailing list rather than commenting on the wiki (wiki discussions get unwieldy fast).

## Motivation

Most data systems provide client tools to connect the data server to inspect data and they will use localhost as the default server(if not specified), for example, `mysql` command will use localhost:3306 if -p and -h are not specified and `zkCli.sh` will use localhost:2181 if -server is not specified, this is convenient when debugging data.

We need to specify --bootstrap-server parameter in almost all command-line tools, which means we would connect to the target server using the ssh command, so it's nicer if we use localhost:9092 as the default bootstrap-server in these commands.

## Public Interfaces

This KIP change an argument of several command-line tools, we already supported--bootstrap-server/broker-list/zookeeper in command-line tools, we will use localhost:9092 as default value if none of these params provided.

Command Name	Status	Changes Needed
kafka-acls.sh	Supports only --bootstrap-server	add default value
kafka-broker-api-versions.sh	Supports only --bootstrap-server	add default value
kafka-cluster.sh	Supports only --bootstrap-server	add default value
kafka-configs.sh	Supports both --zookeeper and --bootstrap-server	add default value if none of -zookeeper and --bootstrap-server provided
kafka-console-consumer.sh	Supports only --bootstrap-server	add default value
kafka-console-producer.sh	Supports --bootstrap-server and --broker-list	add default value if none of -broker-list and --bootstrap-server provided
kafka-consumer-groups.sh	Supports only --bootstrap-server	add default value
kafka-consumer-perf-test.sh	Supports --bootstrap-server and --broker-list	add default value if none of -broker-list and --bootstrap-server provided
kafka-delegation-tokens.sh	Supports only --bootstrap-server	add default value
kafka-delete-records.sh	Supports only --bootstrap-server	add default value
kafka-dump-log.sh	Supports no server	none
kafka-features.sh	Supports only --bootstrap-server	add default value
kafka-get-offsets.sh	Supports --bootstrap-server and --broker-list	add default value if none of -broker-list and --bootstrap-server provided

kafka-leader-election.sh	Supports only ---bootstrap-server	add default value
kafka-log-dirs.sh	Supports only ---bootstrap-server	add default value
kafka-metadata-shell.sh	Supports no server args	none
kafka-producer-perf-test.sh	Supports no server args	none
kafka-reassign-partitions.sh	Supports only --bootstrap-server	add default value
kafka-replica-verification.sh	Supports only --broker-list	add default value
kafka-run-class.sh kafka-server-start.sh kafka-server-stop.sh kafka-storage.sh	Supports no server args	none
kafka-streams-application-reset.sh	Supports only --bootstrap-server	add default value
kafka-topics.sh	Supports only --bootstrap-server	add default value
kafka-transactions.sh	Supports only --bootstrap-server	add default value
kafka-verifiable-consumer.sh kafka-verifiable-producer.sh	Supports --bootstrap-server and --broker-list	add default value if none of -broker-list and --bootstrap-server provided
trogdor.sh	Supports no server args	none
zookeeper-security-migration.sh zookeeper-server-start.sh zookeeper-server-stop.sh zookeeper-shell.sh	Supports only --zookeeper	none

## Proposed Changes

New implementation all these commands does not change the interactions between the tool and the brokers, the only change is they can be used without --bootstrap-server(or broker-list)

1. For commands supports only --bootstrap-server, they will be used without --bootstrap-server and localhost:9092 is the default value.
2. For commands supports only --broker-list, they will be used without --broker-list and localhost:9092 is the default value.
3. For commands supports both --bootstrap-server and --broker-list, localhost:9092 is the default value if both --bootstrap-server and --broker-list are not provided.
4. For commands supports both --zookeeper and --broker-list, localhost:9092 is the default value if both --bootstrap-server and --zookeeper are not provided.

## Compatibility, Deprecation, and Migration Plan

This is a compatible change and any old client tools will still be working normally.

## Rejected Alternatives

For client tools supports only --zookeeper, use localhost:2181 as default zookeeper address, I don't think this is worth doing since KIP-500 is removing all zookeeper code.