

WebHCat Reference GetDB

Describe Database — GET `ddl/database/:db`

- [Describe Database — GET `ddl/database/:db`](#)
 - [Description](#)
 - [URL](#)
 - [Parameters](#)
 - [Results](#)
 - [Example](#)
 - [Curl Command](#)
 - [JSON Output](#)
 - [JSON Output \(error\)](#)

Description

Describe a database. (Note: This resource has a "format=extended" parameter however the output structure does not change if it is used.)

URL

`http://www.myserver.com/templeton/v1/ddl/database/:db`

Parameters

Name	Description	Required?	Default
<code>:db</code>	The database name	Required	None

The [standard parameters](#) are also supported.

Results

Name	Description
<code>location</code>	The database location
<code>params</code>	The database parameters
<code>comment</code>	The database comment
<code>database</code>	The database name

Example

Curl Command

```
% curl -s 'http://localhost:50111/templeton/v1/ddl/database/newdb?user.name=ctdean'
```

JSON Output

```
{  
  "location": "hdfs://localhost:9000/warehouse/newdb.db",  
  "params": "{a=b}",  
  "comment": "Hello there",  
  "database": "newdb"  
}
```

JSON Output (error)

```
{  
  "error": "No such database: newdb",  
  "errorCode": 404  
}
```

Navigation Links

Previous: [GET ddl/database](#)
Next: [PUT ddl/database/:db](#)

General: [DDL Resources](#) – [WebHCat Reference](#) – [WebHCat Manual](#) – [HCatalog Manual](#) – [Hive Wiki Home](#) – [Hive Project Site](#)