

# WebHCat Reference GetTables

## List Tables — GET `ddl/database/:db/table`

- List Tables — GET `ddl/database/:db/table`
  - Description
  - URL
  - Parameters
  - Results
  - Example
    - Curl Command
    - JSON Output
    - JSON Output (error)

### Description

List the tables in an HCatalog database.

### URL

`http://www.myserver.com/templeton/v1/ddl/database/:db/table`

### Parameters

Name	Description	Required?	Default
<code>:db</code>	The database name	Required	None
<code>like</code>	List only tables whose names match the specified pattern	Optional	<code>"**"</code> (List all tables)

The [standard parameters](#) are also supported.

### Results

Name	Description
<code>tables</code>	A list of table names
<code>database</code>	The database name

### Example

#### Curl Command

```
% curl -s 'http://localhost:50111/templeton/v1/ddl/database/default/table?user.name=ctdean&like=m*'
```

#### JSON Output

```
{
  "tables": [
    "my_table",
    "my_table_2",
    "my_table_3"
  ],
  "database": "default"
}
```

#### JSON Output (error)

```
{  
    "errorDetail": "  
        org.apache.hadoop.hive.ql.metadata.HiveException: ERROR: The database defaultsd does not exist.  
            at org.apache.hadoop.hive.ql.exec.DDLTask.switchDatabase(DDLTask.java:3122)  
            at org.apache.hadoop.hive.ql.exec.DDLTask.execute(DDLTask.java:224)  
            at org.apache.hadoop.hive.ql.exec.Task.executeTask(Task.java:134)  
            at org.apache.hadoop.hive.ql.exec.TaskRunner.runSequential(TaskRunner.java:57)  
            at org.apache.hadoop.hive.ql.Driver.launchTask(Driver.java:1332)  
            at org.apache.hadoop.hive.ql.Driver.execute(Driver.java:1123)  
            at org.apache.hadoop.hive.ql.Driver.run(Driver.java:931)  
            at org.apache.hcatalog.cli.HCatDriver.run(HCatDriver.java:42)  
            at org.apache.hcatalog.cli.HCatCli.processCmd(HCatCli.java:247)  
            at org.apache.hcatalog.cli.HCatCli.processLine(HCatCli.java:203)  
            at org.apache.hcatalog.cli.HCatCli.main(HCatCli.java:162)  
            at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)  
            at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:39)  
            at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:25)  
            at java.lang.reflect.Method.invoke(Method.java:597)  
            at org.apache.hadoop.util.RunJar.main(RunJar.java:156)  
        ",  
    "error": "FAILED: Error in metadata: ERROR: The database defaultsd does not exist.",  
    "errorCode": 500,  
    "database": "defaultsd"  
}
```

## Navigation Links

Previous: [DELETE ddl/database/:db](#)  
Next: [GET ddl/database/:db/table/:table](#)

General: [DDL Resources](#) – [WebHCat Reference](#) – [WebHCat Manual](#) – [HCatalog Manual](#) – [Hive Wiki Home](#) – [Hive Project Site](#)